

WAYNE STATE UNIVERSITY 2022 PARKING STRUCTURES #1, #4, #5, & #6 REPAIRS AND MAINTENANCE DETROIT, MICHIGAN


WSU PROJECT NO: 051-350364 (PS #1) 613-350365 (PS #4) 045-350366 (PS #5) 088-350367 (PS #6)

PROJECT NO: 20-002301.00

NO:	SHEET NAME
R-000	COVER SHEET
R-001	GENERAL NOTES & WORK ITEM SCHEDULES
R-002	PHASING PLANS AND NOTES
R-101	STRUCTURE #1 LEVEL 2 FLOOR PLAN
R-102	STRUCTURE #1 LEVEL 3 FLOOR PLAN
R-103	STRUCTURE #1 LEVEL 4 FLOOR PLAN
R-104	STRUCTURE #1 LEVEL 5 FLOOR PLAN
R-105	STRUCTURE #1 LEVEL 6 FLOOR PLAN
R-106	STRUCTURE #4 LEVEL 1 FLOOR PLAN
R-107	STRUCTURE #4 LEVEL 2 FLOOR PLAN
R-108	STRUCTURE #4 LEVEL 3 FLOOR PLAN
R-109	STRUCTURE #4 LEVEL 4 FLOOR PLAN
R-110	STRUCTURE #4 LEVEL 5 FLOOR PLAN
R-111	STRUCTURE #4 LEVEL 6 FLOOR PLAN
R-112	STRUCTURE #4 LEVEL 7 FLOOR PLAN
R-113	STRUCTURE #4 LEVEL 8 & LEVEL 9 FLOOR PLANS
R-114	STRUCTURE #5 LEVEL 2 FLOOR PLAN
R-115	STRUCTURE #5 LEVEL 3 FLOOR PLAN
R-116	STRUCTURE #5 LEVEL 4 FLOOR PLAN
R-117	STRUCTURE #6 LEVEL 1 FLOOR PLAN
R-118	STRUCTURE #6 LEVEL 2 FLOOR PLAN
R-119	STRUCTURE #6 LEVEL 3 FLOOR PLAN
R-120	STRUCTURE #6 LEVEL 4 FLOOR PLAN
R-121	STRUCTURE #6 LEVEL 5 FLOOR PLAN
R-122	STRUCTURE #6 LEVEL 6 FLOOR PLAN
R-123	STRUCTURE #6 LEVEL 7 FLOOR PLAN
R-501	REPAIR DETAILS
R-502	REPAIR DETAILS
R-503	REPAIR DETAILS
R-504	REPAIR DETAILS - W.I. 8.3
R-505	REPAIR DETAILS
R-506	REPAIR DETAILS - W.I. 10.5
R-507	REPAIR DETAILS - W.I. 10.5
R-508	REPAIR DETAILS
R-509	REPAIR DETAILS
R-510	REPAIR DETAILS
R-511	REPAIR DETAILS



525 Avis Drive Suite 1
Ann Arbor, MI 48108
734.663.1070 Ph
walkerconsultants.com



SITE LOCATION MAP

BIDDING & CONSTRUCTION
03/24/2022

J:\20-002301-00-WSU_#1_2022_RepairDrawings\2022 WSU RENOVATIONS.rvt 3/24/2022 2:51:09 PM

GENERAL RESTORATION NOTES

A. CONSTRUCTION

- CONTRACTOR SHALL PERFORM ALL CONSTRUCTION IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE OF MICHIGAN, AND CITY OF DETROIT CODES AND ORDINANCES, INCLUDING FIRE CODES. THE CONTRACTOR SHALL PROMPTLY NOTIFY THE ENGINEER OF ANY KNOWN NONCONFORMITY WITH THE INTENT OF THE CONSTRUCTION DOCUMENTS AND AS-BUILT CONDITIONS TO THE APPLICABLE CODES, LAWS OR ORDINANCES AND REQUEST CLARIFICATION FROM THE ENGINEER PRIOR TO PROCEEDING WITH WORK WHICH IS DEEMED IN CONFLICT WITH THE APPLICABLE CODES, LAWS OR ORDINANCES.
- ALL MATERIAL PROPERTIES SHALL BE AS NOTED IN SPECIFICATIONS.
- PRIOR TO FABRICATION OF ANY MATERIAL OR PLACEMENT OF CONCRETE, FIELD VERIFY ALL EXISTING DIMENSIONS AND CONDITIONS SHOWN ON DRAWINGS. REPORT ALL DISCREPANCIES IN THE FIELD TO ENGINEER IMMEDIATELY.
- DO NOT SCALE DRAWINGS
- DO NOT EXCEED BASE BID QUANTITIES WITHOUT PRIOR WRITTEN APPROVAL FROM OWNER.

B. CONSTRUCTION DOCUMENTS

- CONSTRUCTION DOCUMENTS ENTITLED "WAYNE STATE UNIVERSITY 2022 PARKING STRUCTURES #1, #4, #5, AND #6 REPAIRS AND MAINTENANCE" INCLUDES THESE DRAWINGS AND SEPARATELY BOUND SPECIFICATIONS. FOR PURPOSE OF PERFORMING THE WORK DRAWINGS AND SPECIFICATIONS SHALL BE A SINGLE UNIT. DIMENSIONS SHOWN ON PLANS ARE BASED ON ORIGINAL CONSTRUCTION DOCUMENTS. THE CONTRACTOR IS REQUIRED TO FIELD VERIFY ALL CONDITIONS FOR THE PURPOSES OF PREPARING THE BID AND PERFORMING THE WORK.
- THE EXTENT OF REPAIR AREAS SHOWN ON THE DRAWINGS INDICATES ENGINEER'S ESTIMATES ONLY. THE ESTIMATED UNIT QUANTITIES INCLUDED IN THE BID DOCUMENTS ARE BASED ON ENGINEER'S ESTIMATED UNITS AND ARE FOR BID PURPOSES ONLY. THE CONTRACTOR IS RESPONSIBLE FOR DETERMINING THE ACTUAL EXTENT AND LOCATIONS OF REPAIR AREAS. THE ACTUAL REPAIR QUANTITIES SHALL BE VERIFIED AND AGREED UPON BY THE OWNER AND ENGINEER PRIOR TO COMMENCING THE REPAIR WORK.
- WORK SHALL BE PERFORMED IN COORDINATION WITH CONSTRUCTION OBSERVATIONS BY THE ENGINEER TO DETERMINE IF THE EXPOSED EXISTING CONSTRUCTION IS AS ASSUMED IN THE DESIGN.

C. EXISTING STRUCTURE

- CONSTRUCTION DOCUMENTS RELY ON THE ORIGINAL DRAWINGS. CONTRACTOR TO VERIFY EXISTING CONDITIONS IN FIELD.
- TO THE OWNER/ENGINEER'S KNOWLEDGE, NO OUTSTANDING ENVIRONMENTAL CONCERNS ARE PRESENT ON SITE. IF AN OUTSTANDING ENVIRONMENTAL CONCERN IS IDENTIFIED DURING CONSTRUCTION, THE CONTRACTOR IS TO BRING THIS TO THE ATTENTION OF THE ENGINEER AND OWNER.
- IT IS THE CONTRACTOR'S RESPONSIBILITY TO FAMILIARIZE ITSELF WITH THE ORIGINAL CONSTRUCTION DRAWINGS FOR THE STRUCTURES. ALL SIGNIFICANT DEVIATIONS ARE TO BE BROUGHT TO THE ATTENTION OF THE ENGINEER.

D. DETAILS AND SYMBOLS

- ALL REPAIR DETAILS ARE SHOWN ON DRAWING SERIES R-500.
- DETAILS LABELED "FOR CLARIFICATION ONLY" DO NOT REPRESENT A SEPARATE PRICE ITEM. THESE DETAILS SUPPLEMENT THE BASIC DETAIL TO PROVIDE ADDITIONAL INFORMATION. IN SOME CASES THESE DETAILS SHOW VARIATIONS OF THE TYPICAL CONDITION.
- WHEN THE WORK ITEM BUBBLE IS NOTED (TYP), IT MEANS THE WORK ITEM OCCURS AT ALL LOCATIONS WITH THE APPLICABLE DETERIORATION OR DESIGNATION SYMBOL OCCURS ON A PLAN.
- WHERE (T.A.R.) IS NOTED IT MEANS THERE MAY BE AREAS OF THIS WORK IN ADDITION TO THE PARTICULAR DESIGNATED AREAS.
- WHERE TWO OR MORE WORK ITEM BUBBLES ARE SHOWN GROUPED TOGETHER IT MEANS ANY OR ALL OF THE DESIGNATED WORK MAY BE APPLICABLE. COORDINATION OF WORK ITEMS IS THE CONTRACTOR'S RESPONSIBILITY.
- WHEN WORK ITEMS ARE LISTED AS INCIDENTAL, THIS WORK IS INCLUDED IN THE PAYMENT OF OTHER WORK ITEMS AND DOES NOT HAVE A SEPARATE PRICE.
- WHEN THE DETAIL IS LABELED FOR REFERENCE ONLY IT PROVIDES INFORMATION ABOUT INCIDENTAL WORK AND DOES NOT HAVE A PAY UNIT.
- CONTRACTOR IS RESPONSIBLE FOR DETERMINING ACTUAL EXTENT AND LOCATIONS OF REPAIR AREAS WITH THE SPECIFICATIONS. WORK ITEMS ARE SHOWN ONLY TO REPRESENT THE TYPES OF DETERIORATION.
- SEE WORK ITEM SPECIFICATION FOR INFORMATION REGARDING DETAILS.

E. CONCRETE PROTECTION FOR REINFORCEMENT

- THE FOLLOWING ARE REQUIRED FOR FULL SECTION CONCRETE REPLACEMENT OR PARTIAL DEPTH REPAIRS AS SHOWN ON THE DRAWINGS
- THE MINIMUM CONCRETE PROTECTION FOR REINFORCEMENT SHALL BE PER ACI 318-15.
- MINIMUM COVER FOR REINFORCING IN NON-PRESTRESSED CONCRETE AND NON-POST TENSION MEMBERS.

	CONCRETE COVER (INCHES)
a. SLAB TOP REINFORCEMENT	1 1/2
b. SLAB BOTTOM REINFORCEMENT	3/4
c. BEAM TOP REINFORCEMENT, U.N.	3"
d. BEAM STARTS AT SIDES AND BOTTOM TOP BEING	1 1/2
e. BEAM STARTS AT TOP OF BEING	2 1/2
f. COLUMN TIES	1 1/2

"OR 3X BAR DIAMETER, WHICHEVER IS GREATER.

F. EPOXY COATING FOR REINFORCEMENT AND ANCHORS

- EPOXY COAT ALL REINFORCEMENT, EXCEPT WELDED WIRE REINFORCEMENT, IN CAST IN PLACE CONCRETE

G. SHORING AND BRACING

- THE SCOPE OF THIS PROJECT INVOLVES A SELECTIVE DEMOLITION AND REPAIR OF STRUCTURAL BUILDING ELEMENTS THAT WILL REQUIRE TEMPORARY SHORING OF EXISTING AND NEW CONSTRUCTION TO REMAIN. CONTRACTOR SHALL GENERATE A CONSTRUCTION/SHORING PROGRAM AND SUBMIT TO ENGINEER FOR RECORD TWO (2) WEEKS PRIOR TO THE COMMENCEMENT OF WORK.
- CONTRACTOR SHALL PROVIDE ALL SHORING INCLUDING BRACING, SHEETING, ETC. REQUIRED FOR SAFETY AND PROPER EXECUTION OF THE WORK.
- CONTRACTOR IS SOLEY RESPONSIBLE TO PREPARE SHOP DRAWINGS FOR BRACING / SHORING MEMBERS DESIGNED AND STAMPED/SEALED BY A REGISTERED PROFESSIONAL ENGINEER (REGISTERED IN THE STATE OF MICHIGAN) AND SUBMIT THEM TO THE ENGINEER FOR RECORD.
- THE CONTRACTOR SHALL PROVIDE STAMPED/SIGNED CALCULATIONS, PLANS AND DETAILS FOR THE TEMPORARY SUPPORT OF NEW AND EXISTING CONSTRUCTION TO REMAIN PREPARED BY AN ENGINEER LICENSED TO PRACTICE IN THE STATE OF MICHIGAN.
- THE DESIGN OF THE SHORING AND BRACING MEMBERS SHALL INCLUDE ALL CHANGES IN THE STRUCTURE CAUSED BY THE SHORING AND BRACING.

H. EXISTING SERVICES AND UTILITIES

- CONTRACTOR SHALL REVIEW ALL EXISTING CONDITIONS TO DETERMINE ALL ELECTRICAL AND MECHANICAL SERVICES AND UTILITIES AFFECTED BY THE REPAIR WORK. MAKE ALL NECESSARY TEMPORARY CONNECTIONS TO MAINTAIN EXISTING SERVICES TO ALL AREAS OF THE FACILITIES OR OTHER AREAS (NOT IN CONTRACT) AFFECTED BY WORK. THE CONTRACTOR SHALL SUBMIT THE METHODS AND SCHEDULE OF TEMPORARY CONNECTIONS FOR THE OWNER'S APPROVAL PRIOR TO COMMENCEMENT.
- CONTRACTOR WILL CONTINUE TO USE THE STRUCTURES DURING RESTORATION. CONTRACTOR MUST PHASE AND ARRANGE WORK TO MAINTAIN ACCESS AT ALL TIMES TO ALL AREAS THAT ARE NOT UNDER CONSTRUCTION FOR BOTH VEHICLES AND PEDESTRIANS.
- THE CONTRACTOR SHALL VERIFY WORK HOURS WITH THE OWNER. CONTRACTOR SHALL COORDINATE OFF-HOURS, WEEKEND, AND HOLIDAY WORK WITH OWNER AT LEAST 72 HOURS IN ADVANCE.
- THE CONTRACTOR IS RESPONSIBLE FOR COLLECTION AND REMOVAL OF ALL CONSTRUCTION DEBRIS ON A DAILY BASIS, AND THE SITE SHALL BE LEFT IN A NEAT AND ORDERLY CONDITION, SATISFACTORY TO THE OWNER.
- PROVIDE AND INSTALL TEMPORARY SIGNAGE AND BARRIERS PER W.I. SERIES 1.5 PRIOR TO START OF WORK. REFER TO SECTION 020010 FOR SPECIFIC REQUIREMENTS.
- THE CONTRACTOR IS RESPONSIBLE FOR PROTECTING ALL ADJACENT STRUCTURES, LANDSCAPING, AND OTHER SURFACES AND ITEMS WHICH COULD BE AFFECTED BY THE WORK.
- PROTECT ALL EXISTING CONSTRUCTION AND RESTORE TO EXISTING CONDITION FOLLOWING COMPLETION OF WORK, INCLUDING BUT NOT LIMITED TO: GLASS, DOORS, WALLS, LIGHT FIXTURES, CONDUIT, SECURITY CAMERAS, PIPE, EQUIPMENT, ETC.
- COVER ANY EXISTING SIGNS THAT MAY CONFLICT WITH TEMPORARY TRAFFIC CONTROL SIGNS. REVIEW WITH OWNER PRIOR TO COVERING EXISTING SIGNS. RETURN TO SERVICE UPON COMPLETION OF PROJECT.
- CONTRACTOR SHALL COORDINATE WITH ALL OTHER ONGOING WSU PROJECTS WITHIN AND NEARBY PARKING STRUCTURES & SURROUNDING AREAS.

- EMBEDDED ELECTRICAL CONDUIT MAY BE PRESENT IN SLABS-ON-GROUND AND SUPPORTED SLABS. CONTRACTOR SHALL LOCATE EMBEDDED ITEMS PRIOR TO START OF WORK. CONTRACTOR SHALL TAKE ALL PRECAUTIONS NECESSARY TO AVOID CUTTING/DAMAGING EMBEDDED AND SURFACE MOUNTED CONDUIT/WIRING. IF CONDUIT/WIRING IS DAMAGED AS RESULT OF CONSTRUCTION OPERATIONS, NOTIFY OWNER AND ENGINEER IMMEDIATELY. CONDUIT/WIRING DAMAGE BY CONSTRUCTION OPERATIONS SHALL BE REPAIRED BY CONTRACTOR AT NO COST TO OWNER.
- PROVIDE A MINIMUM 72 HOUR NOTICE TO THE OWNER REPRESENTATIVE PRIOR TO ANY INTERRUPTIONS IN UTILITY SERVICES.
- PRIOR TO START OF WORK, VERIFY STATUS OF EXISTING SECURITY SYSTEMS (IE: IDENTIFY ANY NON-FUNCTIONAL CAMERAS / COMPONENTS). PERFORM SIMILAR REVIEW OF ELEVATORS AND LIGHTING SYSTEMS. PROVIDE WRITTEN DOCUMENTATION AND PHOTOS/VIDEO TO OWNER PRIOR TO COMMENCING WITH REPAIRS.
- CONTRACTOR SHALL PERFORM DETAILED SURVEY TO DOCUMENT EXISTING CONDITIONS AT PARKING STRUCTURES AND ADJACENT AREAS PRIOR TO START OF CONSTRUCTION. SUBMIT WRITTEN DOCUMENTATION AND PHOTOS/VIDEO TO OWNER.
- CONTRACTOR SHALL INSTALL FILTERS ON DRAINS (ALL LEVELS) TO PREVENT DUST/DEBRIS GENERATED FROM CONSTRUCTION FROM ENTERING DRAINAGE SYSTEM, AND REMOVE UPON COMPLETION OF WORK.

I. CONSTRUCTION PHASING, SEQUENCING AND TRAFFIC MAINTENANCE

- WORK SHALL BE COORDINATED WITH THE OWNER'S REPRESENTATIVE AND ALL IDENTIFIED PROJECT REPRESENTATIVES.
- OWNER WILL CONTINUE TO USE STRUCTURES DURING RESTORATION. CONTRACTOR MUST PHASE AND ARRANGE WORK SO AS TO MAINTAIN ACCESS AT ALL TIMES TO ALL AREAS THAT ARE NOT UNDER CONSTRUCTION FOR BOTH VEHICLES AND PEDESTRIANS.
- THE CONTRACTOR SHALL VERIFY WORK HOURS WITH THE OWNER. CONTRACTOR SHALL COORDINATE OFF-HOURS, WEEKEND, AND HOLIDAY WORK WITH OWNER AT LEAST 72 HOURS IN ADVANCE.
- THE CONTRACTOR IS RESPONSIBLE FOR COLLECTION AND REMOVAL OF ALL CONSTRUCTION DEBRIS ON A DAILY BASIS, AND THE SITE SHALL BE LEFT IN A NEAT AND ORDERLY CONDITION, SATISFACTORY TO THE OWNER.
- PROVIDE AND INSTALL TEMPORARY SIGNAGE AND BARRIERS PER W.I. SERIES 1.5 PRIOR TO START OF WORK. REFER TO SECTION 020010 FOR SPECIFIC REQUIREMENTS.
- THE CONTRACTOR IS RESPONSIBLE FOR PROTECTING ALL ADJACENT STRUCTURES, LANDSCAPING, AND OTHER SURFACES AND ITEMS WHICH COULD BE AFFECTED BY THE WORK.
- PROTECT ALL EXISTING CONSTRUCTION AND RESTORE TO EXISTING CONDITION FOLLOWING COMPLETION OF WORK, INCLUDING BUT NOT LIMITED TO: GLASS, DOORS, WALLS, LIGHT FIXTURES, CONDUIT, SECURITY CAMERAS, PIPE, EQUIPMENT, ETC.
- COVER ANY EXISTING SIGNS THAT MAY CONFLICT WITH TEMPORARY TRAFFIC CONTROL SIGNS. REVIEW WITH OWNER PRIOR TO COVERING EXISTING SIGNS. RETURN TO SERVICE UPON COMPLETION OF PROJECT.
- CONTRACTOR SHALL COORDINATE WITH ALL OTHER ONGOING WSU PROJECTS WITHIN AND NEARBY PARKING STRUCTURES & SURROUNDING AREAS.

J. CONCRETE REQUIREMENTS (SEE SECTION 020010 FOR SPECIFIC USES)

- CAST IN PLACE CONVENTIONAL CONCRETE
 - COMPRESSIVE STRENGTH 5000 PSI at 28 DAYS
 - WATER-CEMENT RATIO 0.40 MAX
 - MAX SIZE AGGREGATE 1/2 INCH FOR PARTIAL DEPTH 3/4 INCH FOR FULL DEPTH 6" WITH SUPER PLASTICIZER (AFTER WATER REDUCER ADDITION) 7% ± 1.5%
 - SLUMP (MAXIMUM) 6"
 - AIR CONTENT 5%
 - CEMENTITIOUS ELEVATION 658 LB/C.Y. MIN *
 - MATERIAL CONTENT 3 GAL/CY
 - CORROSIVE INHIBITOR 5% BY WT. OF CEMENT
 - MICROSILICA CONTENT 5%
- PREPACED/CAST REPAIR MATERIAL (033760) COMPRESSIVE STRENGTH: 5000 PSI at 28 DAYS
- ENGINEER SHALL BE NOTIFIED A MINIMUM OF 24 HOURS FOR INSPECTION OF PREPARED CONCRETE SURFACES.

NOTE: CEMENTITIOUS MATERIAL INCLUDES CEMENT, SILICA FUME, AND FLY ASH.

K. GENERAL P-T TENDON REPAIR NOTES:

- TENDONS ARE NEAR THE FLOOR SURFACE AT SPALLS AND DELAMINATIONS. THE CONTRACTOR SHALL EXERCISE EXTREME CAUTION DURING SAWCUTTING AND REMOVALS SO AS NOT TO DAMAGE EXISTING TENDONS OR TENDON SHEATHS. TENDONS MAY BREAK WITH EXPLOSIVE FORCE DURING REMOVALS OR WHEN CUT. CHIPPING WITH 15LB. HAMMERS SHALL BE USED IN LIEU OF SAWCUTTING NEAR SHALLOW TENDONS.
- CAUTION IS REQUIRED WHEN PERFORMING CONCRETE REMOVALS AT BEAMS. ELEVATIONS OF P-T TENDONS BEAMS BE RESPECTED IN INSPECTION OF EXPOSED BEAM TENDONS FOLLOWING CONCRETE REMOVALS. CONTRACTOR IS SOLEY RESPONSIBLE FOR THE FOLLOWING:
 - TRAINING AND MONITORING HIS WORK FORCE CONCERNING THE SAFETY PROCEDURES THAT SHOULD BE EMPLOYED IN THE EXECUTION OF HIS WORK.
 - MAINTAINING STABILITY OF THE STRUCTURE AND ELEMENTS WITHIN THE STRUCTURE, DURING REPAIR WORK, INCLUDING BUT NOT LIMITED TO THE INSTALLATION OF SHORING AND BRACING.
 - WHERE REQUIRED, CONTRACTOR SHALL SUBMIT SEALED DRAWINGS AND CALCULATIONS FROM QUALIFIED PROFESSIONAL ENGINEER, LEGALLY REGISTERED IN STATE OF MICHIGAN TO PERFORM SUCH CALCULATIONS AND DRAWINGS.
- DURING THE REPAIR SEQUENCE, SHORING OF THE FLOOR SLAB MAY BE REQUIRED ALONG THE TENDON RUN. AS A MINIMUM, SHORES SHALL BE INSTALLED AT ALL SITES ALONG THE TENDON RUN WHEN TWO OR MORE ADJACENT TENDON FAILURES OCCUR.
- CONTRACTOR SHALL BE RESPONSIBLE FOR REVIEWING AVAILABLE ORIGINAL DRAWINGS, REVIEW ORIGINAL DRAWINGS AND COORDINATE REPAIR PROCEDURES PRIOR TO PROCEEDING WITH THE WORK. REPRESENTATIVE LOCATIONS OF EXISTING P-T TENDONS AND ANCHORS IN THE FLOOR SLAB ARE SHOWN. EXACT LOCATIONS SHALL BE VERIFIED IN FIELD BY CONTRACTOR PRIOR TO CONCRETE REMOVALS. EXISTING REINFORCING STEEL, NOT SHOWN IN REPAIR DETAILS (UNO), DO NOT CUT ANY REINFORCING UNLESS DIRECTED BY ENGINEER IN WRITING.
- P-T REPAIRS AND DE-TENSIONING PROCEDURES SHALL BE REVIEWED AT PRECONSTRUCTION OR PREINSTALLATION MEETING. NO DEVIATION FROM AGREED UPON PROCEDURES WILL BE ALLOWED UNLESS DIRECTED IN WRITING BY THE ENGINEER. AS A MINIMUM, DURING DETENSIONING OPERATIONS, CLOSE ALL FLOOR SPANS INCLUDING LEVEL BELOW, BEING DETENSIONED, TO PREVENT INJURY IN THE EVENT OF A TENDON POPPING OUT OF THE SLAB.
- NOT ALL TENDON FAILURES ARE IN AREAS OF FLOOR DELAMINATION. PERFORM REMOVAL OF ALL SOUND CONCRETE AS REQUIRED TO EXPOSE TENDONS AND ANCHORS.
- MAINTAIN ORIGINAL TENDON PROFILES WITHIN CONCRETE REMOVAL AREAS. SEE DETAIL 21.0.1 SPECIFIC REQUIREMENTS. DO NOT REMOVE CONCRETE BELOW TENDONS UNLESS REQUIRED BY SPLICING REPAIRS OR TO REPLACE DAMAGED SHEATHING.
- TENDONS MAY OCCUR INDIVIDUALLY OR BUNDLED. USE CAUTION TO AVOID DAMAGE TO TENDONS IN REPAIR AREA. CONTRACTOR CAUSED DAMAGE TO TENDONS SHALL BE REPAIRED AS DIRECTED BY ENGINEER AT NO COST TO OWNER.
- ALL P-T REPAIRS SHALL BE REVIEWED BY ENGINEER PRIOR TO COMMENCING WORK RELATED TO THE P-T REPAIR.
- ALL WORK RELATED TO POST-TENSIONED REPAIRS SHALL BE RESPONSIBILITY OF, AND SHALL BE MONITORED BY, FIRM AND PERSONNEL WITH PTI CERTIFICATION.

L. ABBREVIATIONS

- APPROX = Approximately
- AGG = Aggregate
- BM = Beam
- BOT = Bottom
- CIP = Cast in Place
- CJ = Construction Joint/Control Joint
- CLR = Clearance
- COL = Column
- CONC = Concrete
- DET = Detail
- EA = Each
- E.E. = Each End
- E.S. = Each Side
- EMBED = Embedment Length
- EJ = Expansion Joint
- EXIST = Existing
- FIN = Finished

- FL = Floor
- IN = Inches
- INC = Inclined
- LF = Linear Foot
- LS = Lump Sum
- MAX = Maximum
- MIN = Minimum
- N/A = Not Applicable
- OC = Opposite Corner
- OH = Opposite Hand
- P/C = Precast
- REINF = Reinforcement
- REQD = Required
- SF = Square Foot
- SIM = Similar
- SOG = Slab on Ground
- SPEC = Specification
- SUPT = Supported
- T = Top
- TAR = Typical as Required
- TYP = Typical
- UN or UNO = Unless Noted Otherwise
- WI = Work Item
- WWR = Welded Wire Reinforcement

M. POST-INSTALLED ANCHORS

- WEDGE BOLTS - HLTI KWIK BOLT TZ, UNLESS NOTED.
- ADHESIVE ANCHORS - HLTI HY200, UNLESS NOTED.
- CONTRACTOR SHALL LOCATED EXISTING EMBEDDED REINFORCEMENT USING NON-DESTRUCTIVE TESTING PRIOR TO FABRICATION OF ATTACHMENTS OR DRILLING OF HOLES. NOTIFY ENGINEER OF OBSTRUCTIONS THAT WILL PREVENT INSTALLATION OF ANCHORS AT DESIGN LOCATIONS.
- POST INSTALLED ANCHORS MUST BE INSTALLED USING THE SPACING AND EDGE DISTANCES GIVEN ON THE PLANS OR DETAILS. IF FIELD CONDITIONS DICTATE THAT THE ANCHOR SPACING OR EDGE DISTANCE BE MODIFIED, THE CONTRACTOR SHALL SUBMIT A FIELD SKETCH TO THE ENGINEER FOR REVIEW PRIOR TO MAKING ANY MODIFICATIONS.
- POST INSTALL ANCHOR HOLES SHALL BE DRILLED USING A HAMMER DRILL. CORING DRILLING HOLES WILL NOT BE PERMITTED WITHOUT ENGINEER'S APPROVAL FOR EACH INSTALLATION LOCATION.
- ADHESIVE ANCHORS SHALL BE INSTALLED BY AN ACI-CRSI CERTIFIED "ADHESIVE ANCHOR INSTALLER"

N. NON-SHRINK GROUT

- COMPRESSIVE STRENGTH: 8000 PSI MIN.

O. TESTING & INSPECTION NOTES

- FOLLOWING TESTS AND INSPECTION SHALL BE PERFORMED BY AN INDEPENDENT TESTING AND INSPECTION AGENCY EMPLOYED BY OWNER AND APPROVED BY ENGINEER. TEST AND INSPECTION REPORTS SHALL BE SUBMITTED FOR APPROVAL TO OWNER AND ENGINEER.
- REQUIRED VERIFICATION AND INSPECTION
 - CONCRETE CONSTRUCTION CONT. PERIODIC
 - VERIFYING USE OF REQUIRED DESIGN MIX. X
 - PERFORM SAMPLING AND TESTING OF CONCRETE ACCORDING TO SPECIFICATIONS X
 - INSPECTION FOR MAINTENANCE OF SPECIFIED CURING TEMPERATURE AND TECHNIQUES. X


P. PHASING INSTRUCTION AND NOTES

- DEFINITIONS
 - CONSTRUCTION PHASING, SEQUENCING AND TRAFFIC MAINTENANCE WORK SEQUENCE SHALL BE COORDINATED WITH THE OWNER'S REPRESENTATIVE AND ALL IDENTIFIED PROJECT REPRESENTATIVES. OWNER WILL CONTINUE TO USE STRUCTURES DURING RESTORATION. CONTRACTOR MUST PHASE AND ARRANGE WORK SO AS TO MAINTAIN ACCESS AT ALL TIMES TO AREAS THAT ARE NOT UNDER CONSTRUCTION FOR BOTH VEHICLES AND PEDESTRIANS.
 - PROTECTION ZONE: THIS IS AN AREA THAT IS TAKEN OUT OF SERVICE AND ISOLATED FROM THE GARAGES NORMAL PEDESTRIAN AND VEHICULAR CIRCULATION TO PROTECT THE PATRONS FROM HAZARDS RESULTING FROM WORK BEING PERFORMED ABOVE AND/OR NEARBY WORK THAT REQUIRES PROTECTION ZONES SHALL INCLUDE SHOT BLAST/SEALER APPLICATION (WHEN JOINTS ARE OPEN), CONCRETE DEMOLITION, CONCRETE PLACEMENT, CEILING REMOVAL/SURFACE PREP, WELDING AND SEALANT REPLACEMENT AND ALL OTHER SIMILAR ACTIVITIES THAT MAY CAUSE DISRUPTION TO VEHICLES / PATRONS.
 - WORK ZONE: THIS IS AN AREA THAT IS CAPTURED FOR THE PURPOSE OF PERFORMING PROJECT RELATED WORK ITEMS. THE AREA SHALL BE BARRICADED TO PREVENT GARAGE PATRONS/VEHICLES FROM ENTERING/PARKING WHILE CONTRACTORS ARE IN CONTROL OF THE AREA.
 - WORK PHASE AREA: THIS INCLUDES ALL AREAS AFFECTED BY A PARTICULAR PHASE INCLUDING THE WORK ZONE, PROTECTION ZONE, AND THEIR USE FOR TEMPORARY PEDESTRIAN AND VEHICLE CIRCULATION.
 - PROTECTION PARTITION/BARRICADES: THIS DESCRIBES THE BARRICADES AND PROTECTION ENCLOSURES THAT WILL BE INSTALLED AROUND THE WORK AND PROTECTION ZONES TO KEEP GARAGE PATRONS AND THEIR VEHICLES OUT OF THOSE RESPECTIVE AREAS. IN ADDITION THESE ELEMENTS MUST KEEP DUST AND OTHER CONSTRUCTION RELATED DEBRIS FROM MIGRATING IN THE OCCUPIED AREAS OF THE GARAGE.
- PHASING
 - PHASING SHALL BE AS SCHEDULED BY THE CONTRACTOR AND APPROVED BY THE ENGINEER/OWNER.
 - THE CONTRACTOR SHALL PROVIDE UNOBSTRUCTED PEDESTRIAN ACCESS (PROTECTED WHEN NECESSARY) TO ALL EMERGENCY EGRESS STAIRS AND EXITS AT ALL TIMES. THE CONTRACTOR SHALL INSTALL AND MAINTAIN SIGNAGE THAT CLEARLY DIRECTS PATRONS TO AND FROM THESE DESTINATIONS. THE CONTRACTOR SHALL PROVIDE AND MAINTAIN LIGHTING FOR THESE PHASING IN THE EVENT THE GARAGE LIGHTING IS BLOCKED OR REDUCED BY PROJECT RELATED WORK.
 - IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO CLEAR WORK PHASE AREA OF VEHICLES. THE CONTRACTOR SHALL WORK IN UNISON WITH THE OWNER TO CAPTURE THE AREAS BY INCREMENTALLY INSTALLING BARRICADES TO PREVENT VEHICLES FROM REENTERING THE AREA AS IT IS CLEARED. IN ADDITION TEMPORARY SIGNAGE SHALL BE INSTALLED AND ADJUSTED BY THE CONTRACTOR DURING THE WORK/PROTECTION ZONE CAPTURE EFFORT. NOTE THAT NEW AREAS CANNOT BE CAPTURED PRIOR TO WORK ZONES OR PORTIONS THEREOF BEING RETURNED TO SERVICE SO THAT THE MAXIMUM NUMBER OF SPACES OUT OF SERVICE SHALL NOT BE EXCEEDED. ALLOW 24 HOURS BETWEEN RETURNING SPACES TO SERVICE AND OCCUPYING EQUAL NUMBER OF SPACES FOR THE NEXT PHASE OF WORK.
 - BARRICADES SHALL BE OF SUFFICIENT CONSTRUCTION TO PREVENT INADVERTENT ACCESS BY PATRON VEHICLES AND PEDESTRIANS. THE BARRICADES CAN BE INCORPORATED INTO THE WORK ZONE PROTECTION THAT ARE INTENDED TO PREVENT THE ESCAPE OF DUST AND OTHER DEBRIS FROM THE WORK ZONE.
 - THE FOLLOWING PARAMETERS SHALL BE CONSIDERED WHEN DEVELOPING PHASING PLANS.
 - SEE PHASING NOTES ON SHEET R-002 AND ON PLAN SHEETS FOR STRUCTURE-SPECIFIC PHASING REQUIREMENTS, INCLUDING MAXIMUM PARKING SPACE CLOSURES AND CONSTRUCTION START AND COMPLETION DATES.
- PEDESTRIAN PATH WIDTH(MINIMUM): 6'-0"
- PEDESTRIAN PATH HEADROOM(MINIMUM): 7'-0"
- TEMPORARY VEHICLE ONE-WAY TRAVEL(MINIMUM): 12'-0"
- TEMPORARY VEHICLE HEADROOM: AS POSTED AT GARAGE ENTRANCE
- CONTRACTOR SHALL BE RESPONSIBLE TO LOCKOUT STAIR ACCESS INTO WORK, WORK PHASE, AND AREAS UNDER CONSTRUCTION TO PREVENT UNAUTHORIZED PATRON ACCESS. DOOR SHALL BE SEALED OFF TO PREVENT AIRBORNE DUST FROM ENTERING INTO STAIRWAYS AND ELEVATOR SHAFTS.

PS#5 WORK ITEM SCHEDULE - ALTERNATES

WORK ITEM	DESCRIPTION	UNITS	QUANTITY
1.1	Project Mobilization	L.S.	1
1.5	Temporary Signage & Barriers	L.S.	1
1.6	Means of Access - Exterior Facade	L.S.	1
3.1C	Floor Repair - Partial Depth (P/C Field-Topped)	S.F.	2,300
3.2	Floor Repair - Slab-on-Grade	S.F.	352
3.3C	Floor Repair - Full Depth (P/C Field-Topped)	S.F.	1,400
4.9	Remove Loose Concrete & Coat	L.S.	1
5.1	Beam Repair - Partial Depth (Side)	S.F.	100
5.2	Beam Repair - Partial Depth (Underside)	S.F.	100
6.1	Column Repair - Partial Depth	S.F.	100
7.1	Wall Repair - Partial Depth	S.F.	250
7.2	Wall Repair - Grout Pockets / Connections	Ea.	100
8.1	Tee Stem Repair - Partial Depth	Ea.	2
8.2	Tee Stem Repair - Test Opening	Ea.	2
8.3	Tee Stem Repair - Partially Encased Stem	Ea.	1
8.4	Tee Stem Repair - End Encasement	Ea.	11
8.5	Tee Stem - Cable Repair "Grab-It"	Ea.	2
10.7	Seal Roof Level Joint Between Bays	L.F.	204
10.9	Replace S.O.G. Transition Joint	L.F.	60
11.1	Seal Floor Cracks	L.F.	500
11.2	Replace Joint Sealants (Tee-to-Tee Joints, Joints Along Beams, etc.)	L.F.	13,000
11.4	Tool & Seal Control Joints (For Reference Only)	Incidental	
11.5	Epoxy Injection	L.F.	1,000
11.6	Silicone Encastr	L.F.	400
11.7	Cove Sealant	L.F.	600
16.3	Traffic Topping - Recoat	S.F.	24,000
16.9	Scaled Surface Repair (Epoxy/Sand)	S.F.	2,000
18.1	Temporary Shoring	Ea.	20
25.1	Mechanical / Electrical Allowance	Allow.	1
25.2	Mechanical - Replace Floor Drains	Ea.	5
25.3	Mechanical - Pipe & Hangers	L.F.	40
36.1	Stair Towers - Replace Lintels	Ea.	8
36.2	Stair Towers - Replace CMU Units	Ea.	130
36.3	Stair Towers - Remove Door/Frame and Refinish Opening	Ea.	5
45.1	Paint Traffic Markings	L.S.	1
45.4	Clean / Paint Steel Connections	Ea.	200
50.2	Install Door Sweeps	Ea.	2

Additional Temporary Signage, Temporary Barriers, and Traffic Markings required to perform any Alternate Work Items shall be incidental.



PS#5 - WORK ITEM SCHEDULE - BASE BID

WORK ITEM	DESCRIPTION	UNITS	QUANTITY
1.1	Project Mobilization	L.S.	1
1.5	Temporary Signage & Barriers	L.S.	1
1.6	Means of Access - Exterior Facade	L.S.	1
3.1C	Floor Repair - Partial Depth (P/C Field-Topped)	S.F.	2,300
3.2	Floor Repair - Slab-on-Grade	S.F.	352
3.3C	Floor Repair - Full Depth (P/C Field-Topped)	S.F.	1,400
4.9	Remove Loose Concrete & Coat	L.S.	1
5.1	Beam Repair - Partial Depth (Side)	S.F.	100
5.2	Beam Repair - Partial Depth (Underside)	S.F.	100
6.1	Column Repair - Partial Depth	S.F.	100
7.1	Wall Repair - Partial Depth	S.F.	250
7.2	Wall Repair - Grout Pockets / Connections	Ea.	100
8.1	Tee Stem Repair - Partial Depth	Ea.	2
8.2	Tee Stem Repair - Test Opening	Ea.	2
8.3	Tee Stem Repair - Partially Encased Stem	Ea.	1
8.4	Tee Stem Repair - End Encasement	Ea.	11
8.5	Tee Stem - Cable Repair "Grab-It"	Ea.	2
10.7	Seal Roof Level Joint Between Bays	L.F.	204
10.9	Replace S.O.G. Transition Joint	L.F.	60
11.1	Seal Floor Cracks	L.F.	500
11.2	Replace Joint Sealants (Tee-to-Tee Joints, Joints Along Beams, etc.)	L.F.	13,000
11.4	Tool & Seal Control Joints (For Reference Only)	Incidental	
11.5	Epoxy Injection	L.F.	1,000
11.6	Silicone Encastr	L.F.	400
11.7	Cove Sealant	L.F.	600
16.3	Traffic Topping - Recoat	S.F.	24,000
16.9	Scaled Surface Repair (Epoxy/Sand)	S.F.	2,000
18.1	Temporary Shoring	Ea.	20
25.1	Mechanical / Electrical Allowance	Allow.	1
25.2	Mechanical - Replace Floor Drains	Ea.	5
25.3	Mechanical - Pipe & Hangers	L.F.	40
36.1	Stair Towers - Replace Lintels	Ea.	8
36.2	Stair Towers - Replace CMU Units	Ea.	130
36.3	Stair Towers - Remove Door/Frame and Refinish Opening	Ea.	5
45.1	Paint Traffic Markings	L.S.	1
45.4	Clean / Paint Steel Connections	Ea.	200
50.2	Install Door Sweeps	Ea.	2

PS#5 WORK ITEM SCHEDULE - ALTERNATES

WORK ITEM	DESCRIPTION	UNITS	QUANTITY
8.3A	Tee Stem Repair - Partially Encased Stem (Additional Length)	L.F.	25
11.7	Cove Sealant	L.F.	1,800
16.1	Traffic Topping - New System (Level 2 & Level 3)	S.F.	152,000
26.5	Pressure Test Fire Suppression System	S.F.	1
26.6	Allowance - Standpipe Repairs	Allow.	1
45.2	Paint Standpipes	L.S.	1
45.5	Paint Stair Tower Interiors	Ea.	2

Additional Temporary Signage, Temporary Barriers, and Traffic Markings required to perform any Alternate Work Items shall be incidental.

PS#4 - WORK ITEM SCHEDULE - BASE BID


WORK ITEM	DESCRIPTION	UNITS	QUANTITY
1.1	Project Mobilization	L.S.	1
1.5	Temporary Signage & Barriers	L.S.	1
1.6	Means of Access - Exterior Facade	L.S.	1
3.1B	Floor Repair - Partial Depth (P/T)	S.F.	2,500
3.2	Floor Repair - Slab-on-Grade	S.F.	100
3.3B	Floor Repair - Full Depth (P/T)	S.F.	300
3.4	Floor Repair - Curbs	S.F.	10
3.6	Floor Repair - Slab Edge	S.F.	500
4.1B	Ceiling Repair - Partial Depth (P/T)	S.F.	400
4.9	Remove Loose Concrete & Coat	L.S.	1
5.4	Beam Repair - Partial Depth	S.F.	530
5.5	Beam Repair - Partial Depth at Haunch	S.F.	200
6.1	Column Repair - Partial Depth	S.F.	300
7.1	Wall Repair - Partial Depth	S.F.	300
9.1	Expansion Joint - New Concrete Wash w/ Blockout	L.F.	192
9.2	Expansion Joint - New Concrete Blockout	L.F.	400
9.3	Expansion Joint - New Blockout at Ends	Ea.	4
9.4	Expansion Joint - Blockout Repair (E/S)	S.F.	50
10.3	Expansion Joint - Elastomeric Conc. Edged	L.F.	256
10.4	Expansion Joint - Nosing Repair	L.F.	30
10.5	Expansion Joint - Replace Steel Bearing Angles with Slip Bearing System	Ea.	3
10.6	Replace Stair Tower Isolation Joint	L.F.	38
11.4	Tool and Seal Control Joints (For Reference Only)	Incidental	
16.1	Traffic Topping - New System	Incidental	
18.1	Temporary Shoring	Ea.	50
21.2	Protect Exposed P/T Tendons	Incidental	
21.4	P/T Tendon End Anchorage (Dead)	Ea.	3

P/T Tendon Anchorage - Restressing (if cable fails during stressing under W1 21.6, then restressing shall be paid for under

J:\20-002301-00-WSU_PS_#1_2022_Rpts\Drawings\2022 WSU RENOVATIONS.rvt 3/24/2022 2:51:10 PM


PS #1 PHASING NOTES:

1. CONTRACTOR SHALL BE ALLOWED TO CLOSE A MAXIMUM OF **400 SPACES** AT ONE TIME.
2. ALL VEHICLE ENTRY/EXITS MUST REMAIN OPEN THROUGHOUT DURATION OF PROJECT. WORK AFFECTING STAIRTOWERS, VEHICLE ENTRY/EXITS, & ELEVATORS SHALL BE PERFORMED DURING OFF HOURS. COORDINATE WITH OWNER.
3. CONTRACTOR SHALL SUBMIT PHASING PLAN FOR OWNER/ENGINEER APPROVAL PRIOR TO START OF WORK.
4. PROVIDE OWNER A MINIMUM OF (10) DAYS ADVANCE NOTICE PRIOR TO CLOSING PARKING SPACES.
5. PHASE REPAIRS TO AVOID CREATING DEAD ENDS IN STRUCTURE.
6. INSTALL ALL NECESSARY SIGNAGE AND BARRIERS AS REQUIRED PER W.I. 1.5 PRIOR TO START OF WORK.
7. CONTRACTOR STAGING/PARKING WITHIN THE STRUCTURE SHALL BE IN DESIGNATED WORK AREAS ONLY, SUBJECT TO MAXIMUM PARKING SPACE CLOSURE REQUIREMENTS.
8. CONTRACTOR REQUIRED TO CLEAN EACH WORK AREA TO OWNERS SATISFACTION PRIOR TO RE-OPENING.



PS #4 PHASING NOTES:


1. CONTRACTOR SHALL BE ALLOWED TO CLOSE A MAXIMUM OF **600 SPACES** AT ONE TIME.
2. ALL VEHICLE ENTRY/EXITS MUST REMAIN OPEN DURING DAY TIME HOURS THROUGHOUT DURATION OF PROJECT. WORK AFFECTING STAIRTOWERS, VEHICLE ENTRY/EXITS, & ELEVATOR SHALL BE PERFORMED DURING OFF HOURS. COORDINATE WITH OWNER.
3. CONTRACTOR SHALL SUBMIT PHASING PLAN FOR OWNER/ENGINEER APPROVAL PRIOR TO START OF WORK.
4. PROVIDE OWNER A MINIMUM OF (10) DAYS ADVANCE NOTICE PRIOR TO CLOSING PARKING SPACES.
5. PHASE REPAIRS TO AVOID CREATING DEAD ENDS IN STRUCTURE. SEE TYPICAL WORK AREA ON ISOMETRIC DRAWING TO THE RIGHT.
6. INSTALL ALL NECESSARY SIGNAGE AND BARRIERS AS REQUIRED PER W.I. 1.5 PRIOR TO START OF WORK.
7. CONTRACTOR STAGING/PARKING WITHIN THE STRUCTURE SHALL BE IN DESIGNATED WORK AREAS ONLY, SUBJECT TO MAXIMUM PARKING SPACE CLOSURE REQUIREMENTS.
8. CONTRACTOR REQUIRED TO CLEAN EACH WORK AREA TO OWNERS SATISFACTION PRIOR TO RE-OPENING.



SCHEDULE (APPLIES TO ALL 4 STRUCTURES):
a. CONSTRUCTION START DATE: MAY 2, 2022.
b. SUBSTANTIAL COMPLETION DATE: AUGUST 12, 2022.
c. FINAL COMPLETION DATE: AUGUST 19, 2022.


PS #5 PHASING NOTES:

1. ALL CONCRETE WORK AT PS#5 SHALL BE COMPLETED AND CURED BY NO LATER THAN JULY 26, 2022. CONTRACTOR SHALL REOPEN THE STRUCTURE FOR NORMAL USE ON THE DATES OF JULY 27 THRU JULY 31, 2022. COORDINATE IN ADVANCE WITH OWNER.
2. CONTRACTOR SHALL BE ALLOWED TO CLOSE A MAXIMUM OF **400 PARKING SPACES** AT ONE TIME.
3. THE FOLLOWING PERFORMANCE REQUIREMENTS APPLY TO ALL PARKING SPACE CLOSURES:
 - a. COORDINATE ALL PROJECT ACTIVITIES WITH OTHER ONGOING ACTIVITIES ON CAMPUS. PROVIDE ADVANCE NOTICE OF CONCRETE POURS, MATERIAL DELIVERIES, ETC. THAT MAY AFFECT OTHER ACTIVITIES ON CAMPUS AND COORDINATE WITH WSU.
 - b. ALL VEHICLE ENTRY/EXITS MUST REMAIN OPEN AT ALL TIMES THROUGHOUT DURATION OF PROJECT.
 - c. THE ELEVATOR, STAIR TOWERS, AND ALL SIDEWALKS/ROADWAYS ADJACENT TO STRUCTURE SHALL REMAIN OPEN AND FUNCTIONING AT ALL TIMES FOR DURATION OF PROJECT. CONTRACTOR MAY CLOSE ONE STAIR TOWER AT A TIME AS NEEDED TO COMPLETE REPAIR WORK WITH ADVANCE COORDINATION WITH WSU.
 - d. NO DEAD ENDS ALLOWED.
 - e. CLOSE ALL PARKING AREAS MINIMUM 1 LEVEL BELOW ONGOING CONCRETE REPAIRS.
 - f. PROVIDE WSU A MINIMUM OF (10) DAYS ADVANCE NOTICE BEFORE CLOSING PARKING SPACES, OR FOR NOTIFICATION OF VEHICLES TO BE MOVED FROM WORK AREAS.
4. CONTRACTOR SHALL SUBMIT PHASING PLAN FOR OWNER/ENGINEER APPROVAL PRIOR TO START OF WORK, INCLUDING:
 - a. PROPOSED SEQUENCE, LOCATION, AND DURATION OF REPAIR WORK AT EACH WORK AREA.
 - b. CONTRACTOR PARKING/STAGING (TO OCCUR WITHIN DESIGNATED WORK AREAS ONLY).
 - c. COORDINATION & SCHEDULING OF MATERIAL DELIVERIES, CONCRETE POURS, ETC.
 - d. HOW VEHICLE ENTRY/EXIT & ELEVATOR/STAIRS WILL BE AFFECTED.



PS #6 PHASING NOTES:

1. CONTRACTOR SHALL BE ALLOWED TO CLOSE A MAXIMUM OF **200 SPACES** AT ONE TIME.
2. ALL VEHICLE ENTRY/EXITS MUST REMAIN OPEN THROUGHOUT DURATION OF PROJECT. WORK AFFECTING STAIRTOWERS, VEHICLE ENTRY/EXITS, & ELEVATOR SHALL BE PERFORMED DURING OFF HOURS. COORDINATE WITH OWNER.
3. CONTRACTOR SHALL SUBMIT PHASING PLAN FOR OWNER/ENGINEER APPROVAL PRIOR TO START OF WORK.
4. PROVIDE OWNER A MINIMUM OF (10) DAYS ADVANCE NOTICE PRIOR TO CLOSING PARKING SPACES.
5. PHASE REPAIRS TO AVOID CREATING DEAD ENDS IN STRUCTURE. SEE TYPICAL WORK AREA ON ISOMETRIC DRAWING.
6. INSTALL ALL NECESSARY SIGNAGE AND BARRIERS AS REQUIRED PER W.I. 1.5 PRIOR TO START OF WORK EACH DAY.
7. CONTRACTOR STAGING/PARKING WITHIN THE STRUCTURE SHALL BE IN DESIGNATED WORK AREAS ONLY, SUBJECT TO MAXIMUM CLOSURE REQUIREMENTS.
8. CONTRACTOR REQUIRED TO CLEAN EACH WORK AREA TO OWNERS SATISFACTION PRIOR TO RE-OPENING.



PS #6 ISO PHASING

LEGEND

TYPICAL WORK AREA

WAYNE STATE UNIVERSITY
2022 PARKING STRUCTURES
#1, #4, #5, & #6 REPAIRS AND MAINTENANCE

DETROIT, MICHIGAN




525 Avila Drive, Suite 1
Ann Arbor MI 48108
734.663.1070 Ph
www.walkerconsultants.com

REVISIONS		BIDDING AND CONSTRUCTION	
MARK	DATE	DESCRIPTION	
	03/24/2022		


ISSUE: BIDDING AND CONSTRUCTION
ISSUE DATE: 3/24/2022
PROJECT NO: 20-002301.00
DRAWN BY: ECC
CHECKED BY: DJP / JAD
COPYRIGHT © 2022. ALL RIGHTS RESERVED. NO PART OF THIS DOCUMENT MAY BE REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT PERMISSION FROM WALKER CONSULTANTS, INC.


SHEET TITLE:
PHASING PLANS AND NOTES

R-002



R-101







- REPRESENTATIVE REPAIR LOCATIONS SHOWN. ACTUAL EXTENT AND LOCATION OF REPAIRS TO BE LOCATED AND MARKED FIELD BY THE CONTRACTOR. ALL REPAIRS SHALL BE IN WORK. WORK SHALL BE PERFORMED WITH LOCALIZED PARKING SPACE CLOSURES AS NOTED ON THE PHASING DRAWING. COORDINATE CLOSURES IN ADVANCE WITH WSU. LOCALIZED CLOSURES SHALL NOT CREATE DEAD ENDS AND SHALL MAINTAIN VEHICLE ACCESS TO ALL OPEN AREAS OF THE STRUCTURE. PHASE REPAIRS ACCORDINGLY.
- CONTRACTOR SHALL BE RESPONSIBLE TO PROTECT ALL EXISTING FEATURES FOR DURATION OF PROJECT INCLUDING, BUT NOT LIMITED TO, LIGHT FIXTURES, SURVEYERS, SECURITY SYSTEMS, ELEVATOR CONDUIT, SIGNAGE, DRAINS, PILING, PERIMETER RAILINGS, PERMANENT SHORES, ETC. ANY CONTRACTOR-CAUSED DAMAGE SHALL BE REPAIRED/REPLACED TO SATISFACTION OF OWNER. NO ADDITIONAL COST TO OWNER. REFER TO SECTION 02010 FOR ADDITIONAL REQUIREMENTS. NO LAY OR MAY NOT BE APPLIED TO THE M/E ALLOWANCE (W.1 25.1).
- VERIFY STATUS OF EXISTING SECURITY SYSTEM WITH OWNER (I.E. IDENTIFY ANY NON-FUNCTIONAL CAMERAS/COMPONENTS) PRIOR TO START OF REPAIRS. ANY AND ALL FUNCTIONAL LIGHT FIXTURES SHALL ALSO BE DOCUMENTED PRIOR TO START OF REPAIRS. PERFORM SIMILAR REVIEW AND DOCUMENTATION OF ELEVATORS, PARKING EQUIPMENT, LANDSCAPING, AND OTHER EXISTING CONDITIONS PRIOR TO START OF WORK.
- INSTALL PROTECTIVE MEASURES TO PROTECT OWNERS (WATER PROTECTION, SMOKE ALARM PROTECTION, ETC.) PRIOR TO START OF WORK TO ENSURE ALL DEBRIS/WATER/DUST IS PREVENTED FROM ENTERING ELEVATOR TOWERS. CONTRACTOR SHALL BE RESPONSIBLE FOR ALL CLEANING AND DEBRIS REMOVAL REQUIRED TO RESTORE ELEVATORS TO CLEAN/FUNCTIONAL CONDITION.
- RESTORE ALL LANDSCAPING FEATURES TO EXISTING CONDITION UPON COMPLETION OF ALL WORK (INCIDENTAL). INSTALL ADA-COMPLIANT PEDESTRIAN ROUTES TO STAIR AND ELEVATOR ENTRANCES.
- MAINTAIN PROTECTION FOR FLOOR DRAINS (FILTERS AND OTHER MEANS OF PROTECTION AS NECESSARY) TO PREVENT DEBRIS/WATER FROM ENTERING EXISTING DRAINAGE SYSTEM. CONTRACTOR SHALL BE RESPONSIBLE FOR ANY CLEANING AND REPAIR REQUIRED TO RESTORE EXISTING DRAINAGE SYSTEM TO EXISTING FUNCTIONAL CONDITION (INCLUDING UNDERGROUND PIPING).
- LOCATE CEILING REPAIRS (W.1 4.14.4.2) IN FIELD WITH ELEVATOR. REMOVE ALL CEILING FROM FLOORS ABOVE AND ABOVE LEVELS. LOW AVERAGE WING REPAIR AREAS, W.1.5 4.14.4.2 OCCUR ON MARKINGS OF FIELD SHOWN. APPLY NEW TRAFFIC MARKINGS PER W.1 4.5.1 IN ALL AREAS THROUGHOUT THE STRUCTURE WHERE EXISTING MARKINGS ARE AFFECTED BY PROJECT. SEE SECTION 02010.
- INSTALL, MAINTAIN, AND RELOCATE TEMPORARY SIGNAGE/BARRIERS PER W.1 1.5 PRIOR TO START OF WORK AND AS NEEDED THROUGHOUT THE PROJECT.
- COORDINATE ALL PROJECT ACTIVITIES WITH THE OWNER ON ACTIVITIES ON CAMPUS. PROVIDE ADVANCE NOTICE OF CONCRETE POURS, MATERIAL DELIVERIES, ETC. THAT MAY AFFECT OTHER ACTIVITIES ON CAMPUS AND COORDINATE WITH WSU.
- ALL VEHICLE ENTRY/EXIT MUST REMAIN OPEN AND FUNCTIONAL AT ALL TIMES. IF STAIR TOWERS OPEN, IF CLOSURE IS REQUIRED TO COMPLETE REPAIRS, COORDINATE IN ADVANCE WITH WSU.
- ANY WORK THAT AFFECTS ACCESS TO ELEVATORS OR STAIR TOWERS SHALL BE COORDINATED IN ADVANCE WITH WSU. CONTRACTOR SHALL CLOSE 1 STAIR TOWER AT A TIME WITH ADVANCE APPROVAL.
- NO DEAD ENDS ALLOWED. PHASE REPAIRS ACCORDINGLY. PROVIDE WSU A MINIMUM OF (5) DAYS ADVANCE NOTICE BEFORE CLOSING PARKING SPACES, OR FOR NOTIFICATION TO VISIT TO VIEW THE PROJECT.
- CONTRACTOR SHALL SUBMIT PHASING PLAN FOR OWNER/ENGINEER APPROVAL PRIOR TO START OF WORK.

LEGEND

	W.I. 3.1A, 3.2 - FLOOR REPAIRS
	W.I. 4.1A, 4.2 - CEILING REPAIRS
	W.I. 16.1 TRAFFIC TOPPING - NEW SYSTEM
	W.I. 16.4 TRAFFIC TOPPING - RECOAT



WORK ITEM / DETAIL IDENTIFICATION
(FOR WORK ITEMS WITH DETAILS)



525 Avis Drive, Suite 1
Ann Arbor MI 48108
734.663.1070 Ph
www.walkerconsultants.com


WAYNE STATE UNIVERSITY
2022 PARKING STRUCTURES
#1, #4, #5, & #6 REPAIRS AND MAINTENANCE
DETROIT, MICHIGAN

[illegible]


ISSUE: BIDDING AND CONSTRUCTION	
ISSUE DATE:	3/24/2022
PROJECT NO:	20-002301.00
DRAWN BY:	ECC
CHECKED BY:	DJP
COPYRIGHT © 2022. ALL RIGHTS RESERVED. NO PART OF THIS DOCUMENT MAY BE REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT PERMISSION FROM WALKER CONSULTANTS, INC.	

SHEET TITLE:
STRUCTURE #1
LEVEL 5 FLOOR
PLAN

R-104



1 PS #1 LEVEL 6



SHEET NOTES

1. REPRESENTATIVE REPAIR LOCATIONS SHOWN. ACTUAL EXTENT AND LOCATION OF REPAIRS TO BE LOCATED AND MARKED IN FIELD WITH ENGINEER PRIOR TO START OF WORK. WORK SHALL BE PERFORMED WITH LOCALIZED PARKING SPACE CLOSURES AS NOTED ON THE PHASING DRAWING. COORDINATE CLOSURES IN ADVANCE WITH WSU. LOCALIZED CLOSURES SHALL NOT CREATE DEAD ENDS AND SHALL MAINTAIN VEHICLE ACCESS TO ALL OPEN AREAS OF THE STRUCTURE. PHASE REPAIRS ACCORDINGLY.
2. CONTRACTOR SHALL BE RESPONSIBLE TO PROTECT ALL EXISTING FEATURES FOR DURATION OF PROJECT INCLUDING, BUT NOT LIMITED TO: LIGHT FIXTURES, SWITCHES, SECURITY CAMERAS, ELEVATORS, CONDUIT, SIGNAGE, DRAINS, PIPING, PERIMETER RAILINGS, PERMANENT SHORES, ETC. ANY CONTRACTOR-CAUSED DAMAGE SHALL BE REPAIRED/REPLACED TO SATISFACTION OF OWNER AT NO ADDITIONAL COST TO OWNER. REFER TO SECTION 020010 FOR DESCRIPTION OF WORK THAT MAY OR MAY NOT BE APPLIED TO THE ME ALLOWANCE (W.I. 25.1).
3. VERIFY STATUS OF EXISTING SECURITY SYSTEM WITH OWNER (I.E. IDENTIFY ANY NON-FUNCTIONAL CAMERAS/COMPONENTS) PRIOR TO START OF REPAIRS. ANY NON-FUNCTIONAL LIGHT FIXTURES SHALL ALSO BE DOCUMENTED PRIOR TO START OF REPAIRS. PERFORM SIMILAR REVIEW AND DOCUMENTATION OF ELEVATORS, PARKING EQUIPMENT, LANDSCAPING, AND OTHER EXISTING CONDITIONS PRIOR TO START OF WORK.
4. INSTALL PROTECTION FOR ELEVATOR TOWERS (WATER PROTECTION, SMOKE ALARM PROTECTION, ETC.) PRIOR TO START OF WORK TO ENSURE ALL DEBRIS/WATER (DUST) IS PREVENTED FROM ENTERING ELEVATOR TOWERS. CONTRACTOR SHALL BE RESPONSIBLE FOR ALL CLEANING AND/OR REPAIRS NECESSARY TO RESTORE ELEVATORS TO CLEAN/FUNCTIONAL CONDITION.
5. RESTORE ALL LANDSCAPING FEATURES TO EXISTING CONDITION UPON COMPLETION OF ALL WORK (INCIDENTAL).
6. MAINTAIN ADA-COMPLIANT PEDESTRIAN ROUTES TO STAIR AND ELEVATOR TOWERS AT ALL TIMES.
7. INSTALL PROTECTION FOR FLOOR DRAINS (FILTERS AND OTHER MEANS OF PROTECTION AS NECESSARY) TO PREVENT DEBRIS/WATER FROM ENTERING EXISTING DRAINAGE SYSTEM. CONTRACTOR SHALL BE RESPONSIBLE FOR ANY CLEANING AND/OR REPAIRS NECESSARY TO RESTORE EXISTING DRAINAGE SYSTEM TO EXISTING FUNCTIONAL CONDITION (INCLUDING UNDERGROUND PIPING).
8. LOCATE CEILING REPAIRS (W.I. 4.1A/4.2) IN FIELD WITH ENGINEER. REMOVE ALL LIVE LOADS FROM FLOORS ABOVE AND CLOSE LEVEL BELOW ACTIVE CEILING REPAIR AREAS. W.I.'s 4.1A/4.2 OCCUR ON UNDERSIDE OF LEVEL SHOWN.
9. APPLY NEW TRAFFIC MARKINGS PER W.I. 45.1 IN ALL AREAS THROUGHOUT THE STRUCTURE WHERE EXISTING MARKINGS ARE AFFECTED BY PROJECT. SEE SECTION 020010.
10. INSTALL, MAINTAIN, AND RELOCATE TEMPORARY SIGNAGE/BARRIERS PER W.I. 1.5 PRIOR TO START OF WORK AND AS NEEDED THROUGHOUT THE PROJECT.
11. COORDINATE ALL PROJECT ACTIVITIES WITH OTHER ONGOING ACTIVITIES ON CAMPUS. PROVIDE ADVANCE NOTICE OF CONCRETE POURS, MATERIAL DELIVERIES, ETC. THAT MAY AFFECT OTHER ACTIVITIES ON CAMPUS AND COORDINATE WITH WSU.
12. ALL VEHICLE ENTRY/EXITS MUST REMAIN OPEN AND FUNCTIONAL AT ALL TIMES THAT STRUCTURE IS OPEN. IF CLOSURE IS REQUIRED TO COMPLETE REPAIRS, COORDINATE IN ADVANCE WITH WSU.
13. ANY WORK THAT AFFECTS ACCESS TO ELEVATORS OR STAIR TOWERS SHALL BE COORDINATED IN ADVANCE WITH WSU. CONTRACTOR MAY CLOSE 1 STAIR TOWER AT A TIME WITH ADVANCE APPROVAL.
14. NO DEAD ENDS ALLOWED. PHASE REPAIRS ACCORDINGLY.
15. PROVIDE WSU A MINIMUM OF (5) DAYS ADVANCE NOTICE BEFORE CLOSING PARKING SPACES, OR FOR NOTIFICATION OF VEHICLES TO BE MOVED FROM WORK AREAS.
16. CONTRACTOR SHALL SUBMIT PHASING PLAN FOR OWNER/ENGINEER APPROVAL PRIOR TO START OF WORK.

LEGEND

- W.I. 3.1A, 3.2 - FLOOR REPAIRS
- W.I. 4.1A, 4.2 - CEILING REPAIRS
- W.I. 16.1 TRAFFIC TOPPING - NEW SYSTEM
- W.I. 16.4 TRAFFIC TOPPING - RECOAT
- WORK ITEM/DETAIL NO. (SEE SPECIFICATIONS)
- CLARIFICATION DETAIL NO.
- SHEET NUMBER
- WORK ITEM / DETAIL IDENTIFICATION (FOR WORK ITEMS WITH DETAILS)
- WORK ITEM NUMBER (SEE SPECIFICATIONS)
- WORK ITEM IDENTIFICATION (FOR WORK ITEMS WITHOUT DETAILS)
- NORTH



WAYNE STATE UNIVERSITY
2022 PARKING STRUCTURES
#1, #4, #5, & #6 REPAIRS AND MAINTENANCE
DETROIT, MICHIGAN

MARK	DATE	DESCRIPTION	REVISIONS
	03/24/2022	BIDDING AND CONSTRUCTION	


ISSUE: BIDDING AND CONSTRUCTION
ISSUE DATE: 3/24/2022
PROJECT NO: 20-002301.00
DRAWN BY: ECC
CHECKED BY: DJP


COPYRIGHT © 2022. ALL RIGHTS RESERVED. NO PART OF THIS DOCUMENT MAY BE REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT PERMISSION FROM WALKER CONSULTANTS, INC.

SHEET TITLE:
STRUCTURE #1
LEVEL 6 FLOOR
PLAN

R-105

J:\20-002301-00\WSU_PS_#1_2022_Reps\Drawings\2022 WSU RENOVATIONS.rvt 3/24/2022 2:51:13 PM





A circular compass rose divided into four quadrants by a vertical and a horizontal line. The word "NORTH" is written below the circle, aligned with the top of the vertical line.

DETROIT, MICHIGAN

SHEET TITLE:
STRUCTURE #4
LEVEL 2 FLOOR
PLAN

R-107




CAUTION NOTE:
THE FLOOR SLAB HAS POST-TENSIONING TENDONS. THESE TENDONS ARE NEAR THE FLOOR SURFACE AT SPALLS AND DELAMINATIONS. THE CONTRACTOR SHALL EXERCISE EXTREME CAUTION WHEN SAW-CUTTING SO AS NOT TO DAMAGE EXISTING TENDONS OR TENDON SHEATHS. TENDONS MAY BREAK WITH EXPLOSIVE FORCE WHEN CUT. CHIPPING WITH 15 LB HAMMERS SHALL BE USED IN LIEU OF SAW-CUTTING NEAR SHALLOW TENDONS.



1. REPRESENTATIVE AND GENERAL REPAIR LOCATIONS SHOWN. ACTUAL EXTENT AND EXACT LOCATIONS SHALL BE IDENTIFIED IN FIELD WITH ENGINEER PRIOR TO START OF WORK.
2. PERFORM SEALANT WORK (W/IS 11.1, 11.2, 11.4 & 11.7) IN TRAFFIC TPOING REPAIR AREAS AS NEEDED.
3. REPLACE ALL TRAFFIC MARKINGS THROUGHOUT STRUCTURE PER W/ 45.1. SEE SECTION 02010 FOR SPECIFIC REQUIREMENTS.
4. REMOVE ALL LOOSE SECTIONS OF OVERHEAD CONCRETE THROUGHOUT ENTIRE STRUCTURE PER W/ 4.9 AT START PROJECT. INCLUDES EXTERIOR FACADE.
5. W/IS 3.6, 4.6, 5.4, & 5.5 OCCUR ON UNDERSIDE OF LEVEL SHOWN (TYP). REMAINING WORK ITEMS OCCUR ON TOP OF LEVEL SHOWN.
6. S.O.G CONTAINS EMBEDDED CONDUIT/ WIRING. LOCATE PRIOR TO SAWCUTTING OR CONCRETE REMOVALS. PROCEED WITH CAUTION TO NOT NICK, CUT, OR DAMAGE.
7. FLOOR SLABS CONTAIN EMBEDDED POST-TENSIONED TENDONS. LOCATE PRIOR TO START OF WORK & PERFORM CONCRETE REMOVALS WITH CAUTION TO NOT DAMAGE. NOTIFY ENGINEER OF ANY P/T SYSTEM DETERIORATION UNCOVERED. PERFORM P/T REPAIRS AS NEEDED PER W.I. SERIES 21.0.
8. ALL CONCRETE DEMO & PLACEMENT, AND ALL P/T SYSTEM RELATED WORK AND REPAIRS SHALL BE PERFORMED & SUPERVISED BY FIRM CERTIFIED BY PTI.
9. RESEAL JOINTS, CRACKS PER W.I. SERIES 11.0 WHEN EXPOSED DURING TRAFFIC TPOING REPAIR OPERATIONS.
10. SEE SHEET R-002 FOR PHASING NOTES.

 W.I. SERIES 3.0 - FLOOR SPALL OR DELAMINATION


 W.I. 4.9 OR 5.4 - CEILING / BEAM SPALL OR DELAMINATION

 W.I. SERIES 16.0 - TRAFFIC TOPPING


 EXPANSION JOINT

 FD W.I. 25.2 OR 25.5 - EXISTING FLOOR DRAIN


 SD W.I. 25.4 - NEW SUPPLEMENTAL FLOOR DRAIN


WORK ITEM/DETAIL NO.
(SEE SPECIFICATIONS)
CLARIFICATION DETAIL NO.
SHEET NUMBER


WORK ITEM / DETAIL IDENTIFICATION
(FOR WORK ITEMS WITH DETAILS)


 WORK ITEM NUMBER
(SEE SPECIFICATIONS)

WORK ITEM IDENTIFICATION
(FOR WORK ITEMS WITHOUT DETAILS)


 NORTH

E STATE UNIVER
ARKING STRUC
REPAIRS AND M
DETROIT, MICHIGAN





1. REPRESENTATIVE AND GENERAL REPAIR LOCATIONS SHOWN. ACTUAL EXTENT AND EXACT LOCATIONS SHALL BE IDENTIFIED IN FIELD WITH ENGINEER PRIOR TO START OF WORK.
2. PERFORM SEALANT WORK (W/S 11.1, 11.2, 11.4 & 11.7) IN TRAFFIC TOPPING REPAIR AREAS AS NEEDED.
3. REPLACE ALL TRAFFIC MARKINGS THROUGHOUT STRUCTURE PER W/ 45.1. SEE SECTION 020010 FOR SPECIFIC REQUIREMENTS.
4. REMOVE ALL LOOSE SECTIONS OF OVERHEAD CONCRETE THROUGHOUT ENTIRE STRUCTURE PER W/ 4.9 AT START OF PROJECT. INCLUDES EXTERIOR FACADE.
5. W/S 3.6, 4.1B, 5.4, & 5.5 OCCUR ON UNDERSIDE OF LEVEL SHOWN (TYP). REMAINING WORK ITEMS OCCUR ON TOPSIDE OF LEVEL SHOWN.
6. S.O.G CONTAINS EMBEDDED CONDUIT/ WIRING. LOCATE PRIOR TO SAWCUTTING OR CONCRETE REMOVALS. PROCEED WITH CAUTION TO NOT NICK, CUT, OR DAMAGE.
7. FLOOR SLABS CONTAIN EMBEDDED POST-TENSIONED TENDONS. LOCATE PRIOR TO START OF WORK & PERFORM CONCRETE REMOVALS WITH CAUTION TO NOT DAMAGE. NOTIFY ENGINEER OF ANY P/T SYSTEM DETERIORATION UNCOVERED. PERFORM P/T REPAIRS AS NEEDED PER W.I. SERIES 21.0.
8. ALL CONCRETE DEMO & PLACEMENT, AND ALL P/T SYSTEM RELATED WORK AND REPAIRS SHALL BE PERFORMED & SUPERVISED BY FIRM CERTIFIED BY PTI.
9. RESEAL JOINTS, CRACKS PER W.I. SERIES 11.0 WHEN EXPOSED DURING TRAFFIC TOPPING REMOVAL OPERATIONS.
10. SEE SHEET R-002 FOR PHASING NOTES.



DETROIT, MICHIGAN

ISSUE: BIDDING AND CONSTRUCTION
ISSUE DATE: 3/24/2022
PROJECT NO: 20-002301.00
DRAWN BY: ECC
CHECKED BY: DJP
COPYRIGHT © 2022. ALL RIGHTS RESERVED. NO PART OF THIS DOCUMENT MAY BE REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT PERMISSION FROM WALKER CONSULTANTS, INC.

R-109

 W.I. SERIES 3.0 - FLOOR SPALL OR DELAMINATION
 W.I. 4.9 OR 5.4 - CEILING / BEAM SPALL OR DELAMINATION
 W.I. SERIES 16.0 - TRAFFIC TOPPING
 EXPANSION JOINT
 FD W.I. 25.2 OR 25.5 - EXISTING FLOOR DRAIN
 SD W.I. 25.4 - NEW SUPPLEMENTAL FLOOR DRAIN

WORK ITEM / DETAIL IDENTIFICATION
 (FOR WORK ITEMS WITH DETAILS)


WORK ITEM IDENTIFICATION
 (FOR WORK ITEMS WITHOUT DETAILS)

 NORTH



CAUTION NOTE:
THE FLOOR SLAB HAS POST-TENSIONING TENDONS. THESE TENDONS ARE NEAR THE FLOOR SURFACE AT SPALLS AND DELAMINATIONS. THE CONTRACTOR SHALL EXERCISE EXTREME CAUTION WHEN SAW-CUTTING SO AS NOT TO DAMAGE EXISTING TENDONS OR TENDON SHEATHS. TENDONS MAY BREAK WITH EXPLOSIVE FORCE WHEN CUT. CHIPPING WITH 15 LB HAMMERS SHALL BE USED IN LIEU OF SAW-CUTTING NEAR SHALLOW TENDONS.



1. REPRESENTATIVE AND GENERAL REPAIR LOCATIONS SHOWN. ACTUAL EXTENT AND EXACT LOCATIONS SHALL BE IDENTIFIED IN FIELD WITH ENGINEER PRIOR TO START OF WORK.
2. PERFORM SEALANT WORK (W/S 11.1, 11.2, 11.4 & 11.7) IN TRAFFIC STOPPING REPAIR AREAS AS NEEDED.
3. REPLACE ALL TRAFFIC MARKINGS THROUGHOUT STRUCTURE PER W/ 45.1. SEE SECTION 020010 FOR SPECIFIC REQUIREMENTS.
4. REMOVE ALL LOOSE SECTIONS OF OVERHEAD CONCRETE THROUGHOUT ENTIRE STRUCTURE PER W/ 4.9 AT START OF PROJECT. INCLUDES EXTERIOR FACADE.
5. W/S 3.6, 4.1B, 5.4, & 5.5 OCCUR ON UNDERSIDE OF LEVEL SHOWN (TYP). REMAINING WORK ITEMS OCCUR ON TOP OF LEVEL SHOWN.
6. S.O.G CONTAINS EMBEDDED CONDUIT/ WIRING. LOCATE PRIOR TO SAWCUTTING OR CONCRETE REMOVALS. PROCEED WITH CAUTION TO NOT NICK, CUT, OR DAMAGE.
7. FLOOR SLABS CONTAIN EMBEDDED POST-TENSIONED TENDONS. LOCATE PRIOR TO START OF WORK & PERFORM CONCRETE REMOVALS WITH CAUTION TO NOT DAMAGE. NOTIFY ENGINEER OF ANY P/T SYSTEM DETERIORATION UNCOVERED. PERFORM P/T REPAIRS AS NEEDED PER W.I. SECTION 21.0.
8. ALL CONCRETE DEMO & PLACEMENT, AND ALL P/T SYSTEM RELATED WORK AND REPAIRS SHALL BE PERFORMED & SUPERVISED BY FRM CERTIFIED BY PTI.
9. RESEAL JOINTS CRACKED PER W/ 1. SERIES 11.0 WHEN EXPOSED DURING TRAFFIC STOPPING REMOVAL OPERATIONS.
10. SEE SHEET R-002 FOR PHASING NOTES.



ISSUE:	BIDDING AND CONSTRUCTION
ISSUE DATE:	3/24/2022
PROJECT NO:	20-002301.00
DRAWN BY:	ECC
CHECKED BY:	DJP
COPYRIGHT © 2022. ALL RIGHTS RESERVED. NO PART OF THIS DOCUMENT MAY BE REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT PERMISSION FROM WALKER CONSULTANTS, INC.	

R-110

 W.I. SERIES 3.0 - FLOOR SPALL OR DELAMINATION
 W.I. 4.9 OR 5.4 - CEILING / BEAM SPALL OR DELAMINATION
 W.I. SERIES 16.0 - TRAFFIC TOPPING
 EXPANSION JOINT
 W.I. 25.2 OR 25.5 - EXISTING FLOOR DRAIN
 W.I. 25.4 - NEW SUPPLEMENTAL FLOOR DRAIN
 WORK ITEM / DETAIL NO. (SEE SPECIFICATIONS)
 CLARIFICATION DETAIL NO.
 SHEET NUMBER
 WORK ITEM / DETAIL IDENTIFICATION (FOR WORK ITEMS WITH DETAILS)
 WORK ITEM IDENTIFICATION (FOR WORK ITEMS WITHOUT DETAILS)
 NORTH







CAUTION NOTE:
THE FLOOR SLAB HAS POST-TENSIONING TENDONS. THESE TENDONS ARE NEAR THE FLOOR SURFACE AT SPALLS AND DELAMINATIONS. THE CONTRACTOR SHALL EXERCISE EXTREME CAUTION WHEN SAW-CUTTING SO AS NOT TO DAMAGE EXISTING TENDONS OR TENDON SHEATHS. TENDONS MAY BREAK WITH EXPLOSIVE FORCE WHEN CUT. CHIPPING WITH 15 LB HAMMERS SHALL BE USED IN LIEU OF SAW-CUTTING NEAR SHALLOW TENDONS.

SHEET NOTES (◇ = KEYED NOTES)

1. REPRESENTATIVE AND GENERAL REPAIR LOCATIONS SHOWN. ACTUAL EXTENT AND EXACT LOCATIONS SHALL BE IDENTIFIED IN FIELD WITH ENGINEER PRIOR TO START OF WORK.
2. PERFORM SEALANT WORK (W/S 11.1, 11.2, 11.4 & 11.7) IN TRAFFIC TOPPING REPAIR AREAS AS NEEDED.
3. REPLACE ALL TRAFFIC MARKINGS THROUGHOUT STRUCTURE PER W/ 45.1. SEE SECTION 020010 FOR SPECIFIC REQUIREMENTS.
4. REMOVE ALL LOOSE SECTIONS OF OVERHEAD CONCRETE THROUGHOUT ENTIRE STRUCTURE PER W/ 4.9 AT START OF PROJECT. INCLUDES EXTERIOR FACADE.
5. W/S 3.6, 4.1B, 5.4, & 5.5 OCCUR ON UNDERSIDE OF LEVEL SHOWN (TYP). REMAINING WORK ITEMS OCCUR ON TOPSIDE OF LEVEL SHOWN.
6. S.O.G CONTAINS EMBEDDED CONDUIT/ WIRING. LOCATE PRIOR TO SAWCUTTING OR CONCRETE REMOVALS. PROCEED WITH CAUTION TO NOT NICK, CUT, OR DAMAGE.
7. FLOOR SLABS CONTAIN EMBEDDED POST-TENSIONED TENDONS. LOCATE PRIOR TO START OF WORK & PERFORM CONCRETE REMOVALS WITH CAUTION TO NOT DAMAGE. NOTIFY ENGINEER OF ANY P/T SYSTEM DETERIORATION UNCOVERED. PERFORM P/T REPAIRS AS NEEDED PER W.I. SERIES 21.0.
8. ALL CONCRETE DEMO & PLACEMENT, AND ALL P/T SYSTEM RELATED WORK AND REPAIRS SHALL BE PERFORMED & SUPERVISED BY FIRM CERTIFIED BY PTI.
9. RESEAL JOINTS/CRACKS PER W.I. SERIES 11.0 WHEN EXPOSED DURING TRAFFIC TOPPING REMOVAL OPERATIONS.
10. SEE SHEET R-002 FOR PHASING NOTES.

LEGEND

-  W.I. SERIES 3.0 - FLOOR SPALL OR DELAMINATION
-  W.I. 4.9 OR 5.4 - CEILING / BEAM SPALL OR DELAMINATION
-  W.I. SERIES 16.0 - TRAFFIC TOPPING
-  EXPANSION JOINT
-  FD W.I. 25.2 OR 25.5 - EXISTING FLOOR DRAIN
-  SD W.I. 25.4 - NEW SUPPLEMENTAL FLOOR DRAIN
-  WORK ITEM/DETAIL NO. (SEE SPECIFICATIONS)
CLARIFICATION DETAIL NO.
SHEET NUMBER
- WORK ITEM / DETAIL IDENTIFICATION**
(FOR WORK ITEMS WITH DETAILS)
-  WORK ITEM NUMBER (SEE SPECIFICATIONS)
- WORK ITEM IDENTIFICATION**
(FOR WORK ITEMS WITHOUT DETAILS)
-  NORTH



525 Avis Drive, Suite 1
Ann Arbor MI 48108
734.663.1070 Ph
www.walkerconsultants.com

WAYNE STATE UNIVERSITY
2022 PARKING STRUCTURES
#1, #4, #5, & #6 REPAIRS AND MAINTENANCE


DETROIT, MICHIGAN

[illegible]


ISSUE: BIDDING AND CONSTRUCTION	
ISSUE DATE:	3/24/2022
PROJECT NO:	20-002301.00
DRAWN BY:	ECC
CHECKED BY:	DJP
COPYRIGHT © 2022. ALL RIGHTS RESERVED. NO PART OF THIS DOCUMENT MAY BE REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT PERMISSION FROM WALKER CONSULTANTS, INC.	

SHEET TITLE:
STRUCTURE #4
LEVEL 7 FLOOR
PLAN

R-112



1. REPRESENTATIVE REPAIR LOCATIONS ARE SHOWN. ACTUAL EXTENT AND EXACT LOCATIONS SHALL BE IDENTIFIED IN FIELD WITH ENGINEER PRIOR TO START OF WORK.
2. PERFORM TEST STEM TEST OPENING PER W.I. 8.2 AT LOCATIONS SHOWN. ALLOW ENGINEER TO OBSERVE CONDITIONS AT TEST STEM TEST OPENING, AND REPAIR STEM AS NEEDED / DIRECTED BY ENGINEER PER W.I. SERIES 8.0.
3. W.I.'S 5.1, 5.2, 8.1, 8.2, 8.3, 8.4, AND 8.5, OCCUR ON UNDERSIDE OF LEVEL SHOULDER. REMAINING W.I.'S OCCUR ON TOPSIDE OF LEVEL SHOULDER. VERIFY IN FIELD WITH ENGINEER.
4. SOUND FLOORS AND OBSERVE CEILINGS TO IDENTIFY AND MARK PARTIAL AND FULL-DEPTH FLOOR REPAIR LOCATIONS (W.I. SERIES 3.1C / 3.3C) IN FIELD WITH ENGINEER.
5. INSTALL, MAINTAIN, AND RELOCATE TEMPORARY SIGNAGE AND BARRIERS PER W.I. 1.5 PRIOR TO START OF WORK AND AS NEEDED THROUGHOUT THE PROJECT.
6. REPLACE TRAFFIC MARKINGS (W.I. 45.1) AFTER COMPLETION OF WORK. REFER TO SECTION 020010.
7. REMOVE LOOSE SURFACES OF CONCRETE FROM ALL OVERHEAD SURFACES (ALL LEVELS, INCLUDING EXTERIOR FACADE) PER W.I. 4.9.




DETROIT, MICHIGAN

ND CONST
DE
REVISIONS

SHEET TITLE:
STRUCTURE #5
LEVEL 2 FLOOR
PLAN

R-114

	EXISTING FLOOR DRAIN
	W.I. 3.1C FLOOR REPAIR - PARTIAL DEPTH
	W.I. 3.3C FLOOR REPAIR - FULL DEPTH
	W.I. 16.1 TRAFFIC TOPPING - NEW SYSTEM (ALT)
	W.I. 16.4 TRAFFIC TOPPING - RECOAT
	W.I. 16.9 SCALING REPAIRS
	EXPANSION JOINT (E.J.)






PARKING STRUCTURE #5


-
- NORTH

R-116

525 Avis Drive, Suite 1
Ann Arbor MI 48108
734.663.1070 Ph
www.walkerconsultants.com



1 PS #6 LEVEL 1



SHEET NOTES

- CONTRACTOR SHALL NOT EXCEED BID QUANTITIES WITHOUT WRITTEN AUTHORIZATION FROM OWNER.
- GENERAL FLOOR REPAIR LOCATIONS ARE SHOWN. EXACT LOCATIONS SHALL BE IDENTIFIED IN FIELD WITH ENGINEER PRIOR TO START OF WORK.
- REFER TO DRAWING R-002 FOR PHASING & PARKING SPACE CLOSURE REQUIREMENTS. INSTALL ALL SIGNAGE / BARRIERS PER W.I. 1.5 PRIOR TO START OF WORK.
- ROUTE / SEAL MISC. FLOOR CRACKS ON SUPPORTED LEVELS PER W.I. 11.1.
- REPLACE ALL TEE TO TEE SEALANTS ON LEVELS 6 & 7, AND LOCALIZED TEE TO TEE SEALANTS ON LEVELS 2-5 PER W.I. 11.2. LOCATE LEAKING JOINTS TO BE RESEALED ON LEVELS 2-5 IN FIELD BY OBSERVING UNDERSIDE DURING RAIN EVENT, OR WATER TEST.
- REPLACE ALL WASH & COVE SEALANT ON LEVELS 6 & 7 PER W.I.'S 11.2 & 11.7. REPLACE LOCALIZED WASH AND COVE SEALANTS ON LEVELS 2-5 LOCATED DURING RAIN EVENT.
- INSTALL COATING ON LEVELS 6 & 7 PER W.I. 16.1A, AND NEAR SHEAR WALLS ON ALL SUPPORTED LEVELS PER W.I. 16.1B. SEE ALT. W.I.'S 16.1C & 16.1D FOR OTHER POTENTIAL ALTERNATE COATING WORK. AREAS OF EXISTING COATING THAT OCCUR WHERE NEW COATING IS BEING INSTALLED REQUIRE RECOAT INCIDENTAL TO THIS WORK. SEE SECTION 020010 FOR FURTHER INFORMATION.
- RE-STRIPE PAVEMENT MARKINGS PER REQUIREMENTS OF W.I. 45.1.
- LOCATE SUPPLEMENTAL SHEAR CONNECTOR REPAIRS PER W.I. 50.1 IN FIELD WITH ENGINEER.
- NOTE: BREAK LINES USED ON DRAWINGS TO DENOTE LEVELS DO NOT MATCH EXISTING SIGNAGE IN STRUCTURE.
- REMOVE ALL LOOSE SECTIONS OF OVERHEAD CONCRETE THROUGHOUT STRUCTURE PER W.I. 4.9. INCLUDES REMOVAL OF EXISTING PLYWOOD (TYPICAL LOCATIONS INDICATED ON PLANS) AND LOOSE SECTIONS OF BACKER ROD (NOT SHOWN). CONTRACTOR TO VERIFY REQUIREMENTS IN FIELD.
- SUBMIT PHASING PLAN AND COORDINATE SCHEDULE FOR PERFORMING REPAIRS THAT AFFECT ENTRY / EXITS IN ADVANCE WITH WSU.
- SEE R-002 FOR PHASING AND WORK AREA REQUIREMENTS.
- WALL REPAIRS PER W.I. 7.1 OCCUR ON UNDERSIDE OF LEVEL SHOWN.

WAYNE STATE UNIVERSITY
2022 PARKING STRUCTURES
#1, #4, #5, & #6 REPAIRS AND MAINTENANCE
DETROIT, MICHIGAN




525 Ave. Drive, Suite 1
Ann Arbor MI 48108
734.663.1070 Ph
www.walkerconsultants.com


LEGEND

- FD EXISTING FLOOR DRAIN
- W.I. 3.1D, 3.1E - FLOOR REPAIR - PARTIAL DEPTH
- W.I. 3.2 - FLOOR REPAIR - SLAB ON GRADE
- W.I. 3.3D - FLOOR REPAIR - FULL DEPTH
- EXISTING COATING
- WORK ITEM/DETAIL NO. (SEE SPECIFICATIONS)
- CLARIFICATION DETAIL NO.
- SHEET NUMBER
- WORK ITEM / DETAIL IDENTIFICATION (FOR WORK ITEMS WITH DETAILS)
- WORK ITEM NUMBER (SEE SPECIFICATIONS)
- WORK ITEM IDENTIFICATION (FOR WORK ITEMS WITHOUT DETAILS)
- NORTH

MARK	DATE	BIDDING AND CONSTRUCTION	DESCRIPTION	REVISIONS
	03/24/2022			
ISSUE: BIDDING AND CONSTRUCTION				
ISSUE DATE: 3/24/2022				
PROJECT NO: 20-002301.00				
DRAWN BY: ECC				
CHECKED BY: DJP				
COPYRIGHT © 2022. ALL RIGHTS RESERVED. NO PART OF THIS DOCUMENT MAY BE REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT PERMISSION FROM WALKER CONSULTANTS, INC.				
SHEET TITLE: STRUCTURE #6 LEVEL 1 FLOOR PLAN				
R-117				



1 PS #6 LEVEL 3



SHEET NOTES

- CONTRACTOR SHALL NOT EXCEED BID QUANTITIES WITHOUT WRITTEN AUTHORIZATION FROM OWNER.
- GENERAL FLOOR REPAIR LOCATIONS ARE SHOWN. EXACT LOCATIONS SHALL BE IDENTIFIED IN FIELD WITH ENGINEER PRIOR TO START OF WORK.
- REFER TO DRAWING R-002 FOR PHASING & PARKING SPACE CLOSURE REQUIREMENTS. INSTALL ALL SIGNAGE / BARRIERS PER W.I. 1.5 PRIOR TO START OF WORK.
- ROUTE / SEAL MISC. FLOOR CRACKS ON SUPPORTED LEVELS PER W.I. 11.1.
- REPLACE ALL TEE TO TEE SEALANTS ON LEVELS 6 & 7, AND LOCALIZED TEE TO TEE SEALANTS ON LEVELS 2-5 PER W.I. 11.2. LOCATE LEAKING JOINTS TO BE RESEALED ON LEVELS 2-5 IN FIELD BY OBSERVING UNDERSIDE DURING RAIN EVENT, OR WATER TEST.
- REPLACE ALL WASH & COVE SEALANT ON LEVELS 6 & 7 PER W.I.'S 11.2 & 11.7. REPLACE LOCALIZED WASH AND COVE SEALANTS ON LEVELS 2-5 LOCATED DURING RAIN EVENT.
- INSTALL COATING ON LEVELS 6 & 7 PER W.I. 16.1A, AND NEAR SHEAR WALLS ON ALL SUPPORTED LEVELS PER W.I. 16.1B. SEE ALT. W.I.'S 16.1C & 16.1D FOR OTHER POTENTIAL ALTERNATE COATING WORK. AREAS OF EXISTING COATING THAT OCCUR WHERE NEW COATING IS BEING INSTALLED REQUIRE RECOAT INCIDENTAL TO THIS WORK. SEE SECTION 020010 FOR FURTHER INFORMATION.
- RE-STRIPE PAVEMENT MARKINGS PER REQUIREMENTS OF W.I. 45.1.
- LOCATE SUPPLEMENTAL SHEAR CONNECTOR REPAIRS PER W.I. 50.1 IN FIELD WITH ENGINEER.
- NOTE: BREAK LINES USED ON DRAWINGS TO DENOTE LEVELS DO NOT MATCH EXISTING SIGNAGE IN STRUCTURE.
- REMOVE ALL LOOSE SECTIONS OF OVERHEAD CONCRETE THROUGHOUT STRUCTURE PER W.I. 4.9. INCLUDES REMOVAL OF EXISTING PLYWOOD (TYPICAL LOCATIONS INDICATED ON PLANS) AND LOOSE SECTIONS OF BACKER ROD (NOT SHOWN). CONTRACTOR TO VERIFY REQUIREMENTS IN FIELD.
- SUBMIT PHASING PLAN AND COORDINATE SCHEDULE FOR PERFORMING REPAIRS THAT AFFECT ENTRY / EXITS IN ADVANCE WITH WSU.
- SEE R-002 FOR PHASING AND WORK AREA REQUIREMENTS.
- WALL REPAIRS PER W.I. 7.1 OCCUR ON UNDERSIDE OF LEVEL SHOWN.

LEGEND

- FD EXISTING FLOOR DRAIN
- W.I. 3.1D, 3.1E - FLOOR REPAIR - PARTIAL DEPTH
- W.I. 3.2 - FLOOR REPAIR - SLAB ON GRADE
- W.I. 3.3D - FLOOR REPAIR - FULL DEPTH
- EXISTING COATING
- WORK ITEM/DETAIL NO. (SEE SPECIFICATIONS)
- CLARIFICATION DETAIL NO.
- SHEET NUMBER
- WORK ITEM / DETAIL IDENTIFICATION (FOR WORK ITEMS WITH DETAILS)
- WORK ITEM NUMBER (SEE SPECIFICATIONS)
- WORK ITEM IDENTIFICATION (FOR WORK ITEMS WITHOUT DETAILS)
- NORTH



525 Ave. Drive, Suite 1
Ann Arbor MI 48108
734.663.1070 Ph
www.walkerconsultants.com

WAYNE STATE UNIVERSITY 2022 PARKING STRUCTURES #1, #4, #5, & #6 REPAIRS AND MAINTENANCE


DETROIT, MICHIGAN

MARK	DATE	DESCRIPTION	REVISIONS
	03/24/2022	BIDDING AND CONSTRUCTION	


ISSUE: BIDDING AND CONSTRUCTION
ISSUE DATE: 3/24/2022
PROJECT NO: 20-002301.00
DRAWN BY: ECC
CHECKED BY: DJP
COPYRIGHT © 2022. ALL RIGHTS RESERVED. NO PART OF THIS DOCUMENT MAY BE REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT PERMISSION FROM WALKER CONSULTANTS, INC.

SHEET TITLE:
STRUCTURE #6
LEVEL 3 FLOOR
PLAN

R-119



1 PS #6 LEVEL 5



SHEET NOTES

- CONTRACTOR SHALL NOT EXCEED BID QUANTITIES WITHOUT WRITTEN AUTHORIZATION FROM OWNER.
- GENERAL FLOOR REPAIR LOCATIONS ARE SHOWN. EXACT LOCATIONS SHALL BE IDENTIFIED IN FIELD WITH ENGINEER PRIOR TO START OF WORK.
- REFER TO DRAWING R-002 FOR PHASING & PARKING SPACE CLOSURE REQUIREMENTS. INSTALL ALL SIGNAGE / BARRIERS PER W.I. 1.5 PRIOR TO START OF WORK.
- ROUTE / SEAL MISC. FLOOR CRACKS ON SUPPORTED LEVELS PER W.I. 11.1.
- REPLACE ALL TEE TO TEE SEALANTS ON LEVELS 6 & 7, AND LOCALIZED TEE TO TEE SEALANTS ON LEVELS 2-5 PER W.I. 11.2. LOCATE LEAKING JOINTS TO BE RESEALED ON LEVELS 2-5 IN FIELD BY OBSERVING UNDERSIDE DURING RAIN EVENT, OR WATER TEST.
- REPLACE ALL WASH & COVE SEALANT ON LEVELS 6 & 7 PER W.I.'S 11.2 & 11.7. REPLACE LOCALIZED WASH AND COVE SEALANTS ON LEVELS 2-5 LOCATED DURING RAIN EVENT.
- INSTALL COATING ON LEVELS 6 & 7 PER W.I. 16.1A, AND NEAR SHEAR WALLS ON ALL SUPPORTED LEVELS PER W.I. 16.1B. SEE ALT. W.I.'S 16.1C & 16.1D FOR OTHER POTENTIAL ALTERNATE COATING WORK. AREAS OF EXISTING COATING THAT OCCUR WHERE NEW COATING IS BEING INSTALLED REQUIRE RECOAT INCIDENTAL TO THIS WORK. SEE SECTION 020010 FOR FURTHER INFORMATION.
- RE-STRIPE PAVEMENT MARKINGS PER REQUIREMENTS OF W.I. 45.1.
- LOCATE SUPPLEMENTAL SHEAR CONNECTOR REPAIRS PER W.I. 50.1 IN FIELD WITH ENGINEER.
- NOTE: BREAK LINES USED ON DRAWINGS TO DENOTE LEVELS DO NOT MATCH EXISTING SIGNAGE IN STRUCTURE.
- REMOVE ALL LOOSE SECTIONS OF OVERHEAD CONCRETE THROUGHOUT STRUCTURE PER W.I. 4.9. INCLUDES REMOVAL OF EXISTING PLYWOOD (TYPICAL LOCATIONS INDICATED ON PLANS) AND LOOSE SECTIONS OF BACKER ROD (NOT SHOWN). CONTRACTOR TO VERIFY REQUIREMENTS IN FIELD.
- SUBMIT PHASING PLAN AND COORDINATE SCHEDULE FOR PERFORMING REPAIRS THAT AFFECT ENTRY / EXITS IN ADVANCE WITH WSU.
- SEE R-002 FOR PHASING AND WORK AREA REQUIREMENTS.
- WALL REPAIRS PER W.I. 7.1 OCCUR ON UNDERSIDE OF LEVEL SHOWN.

LEGEND

- ⊖ FD EXISTING FLOOR DRAIN
- W.I. 3.1D, 3.1E - FLOOR REPAIR - PARTIAL DEPTH
- W.I. 3.2 - FLOOR REPAIR - SLAB ON GRADE
- W.I. 3.3D - FLOOR REPAIR - FULL DEPTH
- EXISTING COATING
- WORK ITEM/DETAIL NO. (SEE SPECIFICATIONS)
- CLARIFICATION DETAIL NO.
- SHEET NUMBER
- WORK ITEM / DETAIL IDENTIFICATION (FOR WORK ITEMS WITH DETAILS)
- WORK ITEM NUMBER (SEE SPECIFICATIONS)
- WORK ITEM IDENTIFICATION (FOR WORK ITEMS WITHOUT DETAILS)
- NORTH

WAYNE STATE UNIVERSITY 2022 PARKING STRUCTURES #1, #4, #5, & #6 REPAIRS AND MAINTENANCE


DETROIT, MICHIGAN




525 Ave. Drive, Suite 1
Ann Arbor MI 48108
734.663.1070 Ph
www.walkerconsultants.com

MARK	DATE	DESCRIPTION	REVISIONS
	03/24/2022	BIDDING AND CONSTRUCTION	
ISSUE: BIDDING AND CONSTRUCTION			
ISSUE DATE: 3/24/2022			
PROJECT NO: 20-002301.00			
DRAWN BY: ECC			
CHECKED BY: DJP			
COPYRIGHT © 2022. ALL RIGHTS RESERVED. NO PART OF THIS DOCUMENT MAY BE REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT PERMISSION FROM WALKER CONSULTANTS, INC.			
SHEET TITLE: STRUCTURE #6 LEVEL 5 FLOOR PLAN			

R-121



1 PS #6 LEVEL 6



SHEET NOTES

- CONTRACTOR SHALL NOT EXCEED BID QUANTITIES WITHOUT WRITTEN AUTHORIZATION FROM OWNER.
- GENERAL FLOOR REPAIR LOCATIONS ARE SHOWN. EXACT LOCATIONS SHALL BE IDENTIFIED IN FIELD WITH ENGINEER PRIOR TO START OF WORK.
- REFER TO DRAWING R-002 FOR PHASING & PARKING SPACE CLOSURE REQUIREMENTS. INSTALL ALL SIGNAGE / BARRIERS PER W.I. 1.5 PRIOR TO START OF WORK.
- ROUTE / SEAL MISC. FLOOR CRACKS ON SUPPORTED LEVELS PER W.I. 11.1.
- REPLACE ALL TEE TO TEE SEALANTS ON LEVELS 6 & 7, AND LOCALIZED TEE TO TEE SEALANTS ON LEVELS 2-5 PER W.I. 11.2. LOCATE LEAKING JOINTS TO BE RESEALED ON LEVELS 2-5 IN FIELD BY OBSERVING UNDERSIDE DURING RAIN EVENT, OR WATER TEST.
- REPLACE ALL WASH & COVE SEALANT ON LEVELS 6 & 7 PER W.I.'S 11.2 & 11.7. REPLACE LOCALIZED WASH AND COVE SEALANTS ON LEVELS 2-5 LOCATED DURING RAIN EVENT.
- INSTALL COATING ON LEVELS 6 & 7 PER W.I. 16.1A, AND NEAR SHEAR WALLS ON ALL SUPPORTED LEVELS PER W.I. 16.1B. SEE ALT. W.I.'S 16.1C & 16.1D FOR OTHER POTENTIAL ALTERNATE COATING WORK. AREAS OF EXISTING COATING THAT OCCUR WHERE NEW COATING IS BEING INSTALLED REQUIRE RECOAT INCIDENTAL TO THIS WORK. SEE SECTION 020010 FOR FURTHER INFORMATION.
- RE-STRIPE PAVEMENT MARKINGS PER REQUIREMENTS OF W.I. 45.1.
- LOCATE SUPPLEMENTAL SHEAR CONNECTOR REPAIRS PER W.I. 50.1 IN FIELD WITH ENGINEER.
- NOTE: BREAK LINES USED ON DRAWINGS TO DENOTE LEVELS DO NOT MATCH EXISTING SIGNAGE IN STRUCTURE.
- REMOVE ALL LOOSE SECTIONS OF OVERHEAD CONCRETE THROUGHOUT STRUCTURE PER W.I. 4.9. INCLUDES REMOVAL OF EXISTING PLYWOOD (TYPICAL LOCATIONS INDICATED ON PLANS) AND LOOSE SECTIONS OF BACKER ROD (NOT SHOWN). CONTRACTOR TO VERIFY REQUIREMENTS IN FIELD.
- SUBMIT PHASING PLAN AND COORDINATE SCHEDULE FOR PERFORMING REPAIRS THAT AFFECT ENTRY / EXITS IN ADVANCE WITH WSU.
- SEE R-002 FOR PHASING AND WORK AREA REQUIREMENTS.
- WALL REPAIRS PER W.I. 7.1 OCCUR ON UNDERSIDE OF LEVEL SHOWN.

LEGEND

- ⊖ FD EXISTING FLOOR DRAIN
- W.I. 3.1D, 3.1E - FLOOR REPAIR - PARTIAL DEPTH
- W.I. 3.2 - FLOOR REPAIR - SLAB ON GRADE
- W.I. 3.3D - FLOOR REPAIR - FULL DEPTH
- EXISTING COATING
- WORK ITEM/DETAIL NO. (SEE SPECIFICATIONS)
- CLARIFICATION DETAIL NO.
- SHEET NUMBER
- WORK ITEM / DETAIL IDENTIFICATION (FOR WORK ITEMS WITH DETAILS)
- WORK ITEM NUMBER (SEE SPECIFICATIONS)
- WORK ITEM IDENTIFICATION (FOR WORK ITEMS WITHOUT DETAILS)
- NORTH



525 Ave. Drive, Suite 1
Ann Arbor MI 48108
734.663.1070 Ph
www.walkerconsultants.com

WAYNE STATE UNIVERSITY
2022 PARKING STRUCTURES
#1, #4, #5, & #6 REPAIRS AND MAINTENANCE
DETROIT, MICHIGAN

MARK	DATE	DESCRIPTION	REVISIONS
	03/24/2022	BIDDING AND CONSTRUCTION	

ISSUE: BIDDING AND CONSTRUCTION
ISSUE DATE: 3/24/2022
PROJECT NO: 20-002301.00
DRAWN BY: ECC
CHECKED BY: DJP

COPYRIGHT © 2022. ALL RIGHTS RESERVED. NO PART OF THIS DOCUMENT MAY BE REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT PERMISSION FROM WALKER CONSULTANTS, INC.

SHEET TITLE:
STRUCTURE #6
LEVEL 6 FLOOR
PLAN

R-122

- NOTES:**
1. SANDBLAST AND EPOXY COAT ALL BROKEN TEE FLANGE SHEAR CONNECTORS, (OR REMOVE) AND EPOXY ANCHOR (2) ADDITIONAL #4 BY 3'-0" LONG ACROSS JOINT @ MID DETAIL AS DIRECTED BY ENGINEER. (INCIDENTAL).
 2. PROVIDE 1/2" COVER OVER ALL REINFORCEMENT.
 3. REINFORCING STEEL INSTALLATION REQUIRED ON THIS DETAIL IS INCIDENTAL TO THIS WORK ITEM.
 4. MINIMUM LAP SPLICE FOR #4 BARS IS 20"
 5. **CAUTION:** JUNCTION BOXES AND CONDUIT / WIRING ARE PRESENT IN TOPPING CONCRETE. LOCATE CONDUIT PRIOR TO START OF WORK AND PERFORM REMOVALS IN MANNER TO NOT DAMAGE. COORDINATE WITH WSU TO POWER OFF CIRCUITS PRIOR TO START OF WORK. PERFORM ANY NECESSARY ELECTRICAL REPAIRS UNDER ALLOWANCE W.I. 25.1. TEST AND CONFIRM ALL CIRCUITS AND WIRING ARE PROPERLY OPERATING TO AVOID CONCRETE REPAIRS.
 6. PERFORM FULL DEPTH REMOVALS TO MAINTAIN AN INWARD ANGLE AROUND THE REPAIR PERIMETER AS SHOWN.
 7. ACTUAL THICKNESS OF SLAB VARIES. CONTRACTOR RESPONSIBLE FOR REMOVAL DEPTHS UP TO 7" (AS SHOWN). INCLUDE IN SUBMITTED UNIT PRICE. NO EXTRAS ALLOWED.

FLOOR REPAIR -
FULL DEPTH (P/C FIELD-TOPPED)

3.3C (PS #5)

- NOTES:
1. REFER TO DETAIL SERIES 21.0 FOR PIT REPAIR REQUIREMENTS.
 2. SPACING AND LOCATION OF PIT TENDONS UNKNOWN. CONTRACTOR TO V.I.F.
 3. REFER TO SECTION 025140 FOR SANDBLASTING AND SURFACE PREPARATION REQUIREMENTS.
 4. PROVIDE SUPPLEMENTAL REINFORCEMENT AS SHOWN (INCIDENTAL).

FLOOR REPAIR -
FULL DEPTH (P/T)

3.3B (PS #4)

-
- VARIES
- SAWCUT PATCH PERIMETER 3/4" (TYP)
- 3" (MIN) (TYP)
- PROVIDE CONTINUOUS #4'S @ 18" O.C. (TYP). DOWELED @ ENDS.
- ORIGINAL SURFACE
- 6" (WF)
- 20" LAP (TYP)
- CONCRETE SLAB (TYP)
- REMOVAL LIMITS (TYP)
- NOTE 2
- REMOVE & REPLACE CONCRETE WITHIN SECTION SHOWN SHADED.
- EXISTING EMBEDDED CONDUIT (ACTUAL SIZE AND LOCATION UNKNOWN). SEE NOTE 1.
- PROVIDE #4 DOWELS w/ 8" MIN. EMBEDMENT @ 18" O.C. (TYP) AROUND PERIMETER OF REPAIR.
- GRIND OR SAWCUT PATCH PERIMETER 1/2" (TYP)
- EXISTING REINFORCEMENT (TYP). LOCATIONS APPROXIMATE. DO NOT CUT, CLEAN AND EPOXY COAT ALL EXPOSED REINF (EXCEPT WIRE).
- PROVIDE 3/4" CLEARANCE AROUND ALL EXPOSED REINF WHERE REQ'D AS SPECIFIED IN SECTION "SURFACE PREPARATION FOR PATCHING AND OVERLAY".
- NOTES:
1. LOCATE EXISTING EMBEDDED CONDUIT / WIRING PRIOR TO START OF REMOVALS. PROCEED WITH CAUTION TO NOT DAMAGE, CUT OR NICK.
 2. CONTRACTOR SHALL PROVIDE/REMOVE FILL AS NECESSARY & COMPACT PRIOR TO POURING CONCRETE. (INCIDENTAL TO THIS WORK)

FLOOR REPAIR - SLAB-ON-GRADE

3.2 (PS#1, PS#4, PS#5, PS#6)

-
- Diagram illustrating the repair of a pre-topped double tee. The diagram shows a cross-section of the concrete structure with a central repair area. Key dimensions and labels include:
- SAWCUT PATCH PERIMETER 3/4" (TYP)**: Dimension for the sawcut patch perimeter.
 - VARIES**: Dimension for the width of the repair area.
 - ORIGINAL SURFACE OF PRE-TOPPED DOUBLE TEE**: Label for the original concrete surface.
 - 1 1/2" - 2 1/2" TYP**: Dimension for the depth of the repair area.
 - SPALL OR DELAMINATION**: Label for the damaged area being repaired.
 - EXIST. P/C PRE-TOPPED TEE (TEE STEMS NOT SHOWN)**: Label for the existing pre-topped tee.
 - REMOVE & REPLACE CONCRETE WITHIN SECTION SHOWN**: Label for the repair area.
 - W.W.R. TO REMAIN (TYP.) LOCATION APPROXIMATE (DO NOT DAMAGE); CLEAN ALL EXPOSED MESH; PROVIDE 3/4" CLEARANCE AROUND ALL EXPOSED REINF. WHERE REQ'D AS SPECIFIED IN SECTION "SURFACE PREPARATION FOR PATCHING AND OVERLAY".**: Detailed instructions for the repair process.

FLOOR REPAIR - PARTIAL DEPTH
(PRE-TOPPED)

3.1E (PS #6)

-
- Diagram illustrating the repair of a precast double tee flange. The diagram shows a cross-section of the flange with various dimensions and annotations:
- EDGE OF SLAB**: Indicated on the left side.
 - SAVE EXISTING REINFORCEMENT (ACTUAL SIZE AND SPACING UNKNOWN). CLEAN AND EPOXYCOAT EXPOSED REINFORCEMENT. PROVIDE 1/2" CLEARANCE AROUND ALL EXPOSED REINF.**: Annotation for the top reinforcement area.
 - EXISTING W.W.R. PROVIDE NEW W.W.R. 4x4-W4.0xW4.0 IN CONCRETE PATCH AREA.**: Annotation for the top reinforcement area.
 - CAST IN PLACE CONCRETE WASH.**: Annotation for the top reinforcement area.
 - PROVIDE SEALANT JOINT PER W.I. 11.5.**: Annotation for the joint area.
 - PRECAST DOUBLE TEE FLANGE.**: Annotation for the right side of the flange.
 - 4"-5" (VIF)**: Vertical dimension on the left side.
 - 3'-0" (VIF)**: Horizontal dimension at the bottom.
 - REMOVE AND REPLACE CONCRETE WITHIN SECTION SHOWN SHADED.**: Annotation for the shaded repair area.
 - NOTE 2**: Annotation pointing to the shaded area.
- NOTES:**
1. PROVIDE 1/2" SAWCUT AROUND PATCH PERIMETER. (TYP)
 2. PERFORM REMOVALS IN A MANNER THAT WILL NOT DAMAGE PRECAST DOUBLE TEE FLANGE OR EMBEDDED REINFORCEMENT. ADJUST REMOVAL EQUIPMENT AS NECESSARY.
 3. CONTRACTOR SHALL SOUND CONCRETE TO LOCATE DETERIORATED AREAS (NOT ALL REPAIR AREAS EXTEND TO EDGE OF SLAB AS SHOWN). VERIFY REIN. LOCATIONS IN FIELD WITH ENGINEER.
 4. EXISTING EMBEDDED WELDED PLATE CONNECTIONS NOT SHOWN. DO NOT DAMAGE DURING CONCRETE REMOVALS. CLEAN / PAINT PRIOR TO PLACEMENT OF REPAIR MATERIAL. (INCIDENTAL). RE-WELD AS NECESSARY PRIOR TO PLACING CONCRETE. (INCIDENTAL)
 5. MAXIMUM 15 LB CHIPPING HAMMERS OR AS DIRECTED BY ENGINEER TO MINIMIZE DAMAGE TO PRECAST DOUBLE TEE FLANGE AND TO PREVENT FULL-DEPTH REMOVAL OF OTHERWISE SOUND PRECAST CONCRETE.

FLOOR REPAIR - PARTIAL DEPTH
(CONCRETE WASHES)

3.1D (PS #6)

-
- INCIDENTAL: INSTALL TRAFFIC COATING ON REPAIR SURFACES PER REQUIREMENTS OF W.I. SERIES 16.0. OVERLAP MIN. 4" ONTO SOUND ADJACENT COATING
- Labels and Dimensions:
- 43'-5" (VIF) SEE NOTE 2
 - 42" (VIF)
 - SAWCUT PATCH PERIMETER 3/4" (TYP.)
 - ORIGINAL SURFACE
 - VARIABLES
 - CONCRETE TOPPING
 - P/C TEE FLANGE
 - REINFORCEMENT TO REMAIN (TYP.)
 - LOCATIONS APPROXIMATE: CLEAN AND EPOXY COAT ALL EXPOSED REINF. (MESH DOES NOT REQUIRE EPOXY COATING). PROVIDE 3/4" CLEARANCE AROUND ALL EXPOSED REINF. WHERE REQ'D AS SPECIFIED IN SECTION "SURFACE PREPARATION FOR PATCHING AND OVERLAY".
 - SPALL OR DELAMINATION
 - REMOVAL LIMITS
 - P/C STEM BELOW
 - REMOVE AND REPLACE CONCRETE WITHIN SECTION SHOWN SHADED
- NOTES:
1. PROVIDE TOOLED JOINTS IN REPAIR AREAS AS REQUIRED TO MAINTAIN EXISTING JOINT LAYOUT PER W.I.
 2. ACTUAL DEPTH OF REQUIRED REMOVALS VARIES. CONTRACTOR RESPONSIBLE FOR REMOVAL DEPTHS 5" (AS SHOWN). INCLUDE IN SUBMITTED UNIT PRICE; NO EXTRAS ALLOWED. DO NOT EXTEND REMOVALS BELOW TOP SURFACE OF TEE FLANGE.
 3. **CAUTION:** JUNCTION BOXES AND CONDUIT / WIRING ARE LOCATED IN TOPPING CONCRETE. LOCATE PRIOR TO START OF WORK AND PERFORM REMOVALS IN MANNER TO NOT DAMAGE EMBEDDED CONDUIT / WIRING. COORDINATE WITH WSI TO POWER OFF CIRCUITS PRIOR TO START OF WORK. PERFORM ANY NECESSARY ELECTRICAL REPAIRS UNDER ALLOWANCE W.I. 25.1. TEST AND CONFIRM ALL CIRCUITS AND LIGHTS ARE WORKING PRIOR TO PLACING CONCRETE.

FLOOR REPAIR -
PARTIAL DEPTH (P/C FIELD-TOPPED)

3.1C (PS #5)

-
- SAWCUT PATCH PERIMETER 1/2" (TYP.)
- INCIDENTAL: INSTALL COATING SYSTEM ON BARE CONCRETE REPAIR SURFACES PER W.I. 16.1, OVERLAP MIN. 4" ONTO SUNK ADJACENT EXISTING COATING.
- VARIABLES
- 6"-7"
- 1/2"
- P/T SLAB
- P/T TENDONS (TYP) DEPTH VARIES
- REINFORCEMENT (TYP.), LOCATIONS APPROXIMATE. INCLUDES MILD STEEL BARS AND P/T TENDONS. REPAIR DAMAGED SHEATHING AS REQUIRED PER DETAIL SERIES 21.0. CLEAN AND EPOXY COAT ALL EXPOSED REINF. PROVIDE 3/4" CLEARANCE AROUND ALL EXPOSED REINF. WHERE REQ'D AS SPECIFIED IN SECTION "SURFACE PREPARATION FOR PATCHING AND OVERLAY".
- SPALL OR DELAMINATION
- REMOVAL LIMITS
- REMOVE & REPLACE CONCRETE WITHIN SECTION SHOWN SHADED.
- CAUTION NOTE:
THE FLOOR SLAB HAS POST-TENSIONING TENDONS. THESE TENDONS ARE NEAR THE FLOOR SURFACE AT SPALLS AND DELAMINATIONS. THE CONTRACTOR SHALL EXERCISE EXTREME CAUTION WHEN SAW-CUTTING SO AS NOT TO DAMAGE EXISTING TENDONS OR TENDON SHEATHS. TENDONS MAY BREAK WITH EXPLOSIVE FORCE WHEN CUT. CHIPPING WITH 15 LB HAMMERS SHALL BE USED IN LIEU OF SAW-CUTTING NEAR SHALLOW TENDONS.

FLOOR REPAIR - PARTIAL DEPTH (P/T)

3.1B (PS #4)

-
- SAWCUT PATCH PERIMETER 3/4" (TYP.)
- ORIGINAL SURFACE
- VARIES 10"-16"
- 4" MIN.
- VARIES
- INSTALL TRAFFIC COATING ON ALL REPAIR SURFACES PER REQUIREMENTS OF W.I. SERIES 16.0 (INCIDENTAL TO W.I. 3.1).
- 4"-6"
- EXISTING CONCRETE SLAB
- REINFORCEMENT (TYP.), LOCATIONS APPROXIMATE. CLEAN AND EPOXY COAT ALL EXPOSED REINF. PROVIDE 3/4" CLEARANCE AROUND ALL EXPOSED REINF. WHERE REQ'D AS SPECIFIED IN SECTION "SURFACE PREPARATION FOR PATCHING".
- SPALL OR DELAMINATION
- REMOVAL LIMITS
- REMOVE AND REPLACE CONCRETE WITHIN SECTION SHOWN SHADED

FLOOR REPAIR - PARTIAL DEPTH


3.1A (PS #1)

[illegible]


ISSUE: BIDDING AND CONSTRUCTION	
ISSUE DATE:	3/24/2022
PROJECT NO:	20-002301.00
DRAWN BY:	Author
CHECKED BY:	Checker
COPYRIGHT © 2022. ALL RIGHTS RESERVED. NO PART OF THIS DOCUMENT MAY BE REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT PERMISSION FROM WALKER CONSULTANTS, INC.	

SHEET TITLE:
REPAIR DETAILS

ED




6.1 COLUMN REPAIR - PARTIAL DEPTH
(PS #1, PS #4, PS #5, PS #6)




- NOTES:
1. CLEAN AND PREPARE REPAIR SURFACES PER REQUIREMENTS OF SECTION 025140.
 2. CLEAN AND EPOXY COAT ALL EXPOSED EXISTING REINFORCEMENT.
 3. ALLOW ENGINEER TO OBSERVE REPAIR CAVITIES & SUPPLEMENTAL REINFORCEMENT PRIOR TO INSTALLING FORMWORK.

5.4 BEAM REPAIR-PARTIAL DEPTH
(PS #4)
5.5 BEAM REPAIR-PARTIAL DEPTH AT HAUNCH
(PS #4)



5.1 BEAM REPAIR-PARTIAL DEPTH (SIDE)
(PS #5)
5.2 BEAM REPAIR-PARTIAL DEPTH (UNDERSIDE)
(PS #5)




- NOTES:
1. ACCESS TO THESE EXTERIOR FACADE ITEMS SHALL BE PER W.I. 1.6 AT PS #4. SEE SECTION 020010 FOR FURTHER REQUIREMENTS.
 2. CONDITION AT PS #4 SHOWN.


4.9 REMOVE LOOSE CONCRETE & COAT
(PS #1, PS #4, PS #5, & PS #6)

7.1 WALL REPAIR - PARTIAL DEPTH
(PS #4)


10.8 EXPANSION JOINT - PRECOMPRESSED VERTICAL SEAL
(PS #4) (ALTERNATE)




4.2 CEILING REPAIR - PARTIAL DEPTH AT DROP PANEL
(PS #1)




4.1B CEILING REPAIR-PARTIAL DEPTH (P/T)
(PS #4)




4.1A CEILING REPAIR - PARTIAL DEPTH
(PS #1)



3.6 FLOOR REPAIR - SLAB EDGE
(PS #4)



3.4 FLOOR REPAIR-CURBS
(PS #4)













3.3D FLOOR REPAIR - FULL DEPTH (CONCRETE WASHES)
(PS #6)

BIDDING AND CONSTRUCTION		REVISIONS
MARK	DATE	
	03/24/2022	

ISSUE: BIDDING AND CONSTRUCTION
ISSUE DATE: 3/24/2022
PROJECT NO: 20-002301.00
DRAWN BY: Author
CHECKED BY: Checker


COPYRIGHT © 2022. ALL RIGHTS RESERVED. NO PART OF THIS DOCUMENT MAY BE REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT PERMISSION FROM WALKER CONSULTANTS, INC.

SHEET TITLE:
REPAIR DETAILS



REPAIR SEQUENCE


1. REMOVE ALL PARKING LIVE LOADS FROM DOUBLE TEE (AND 3 LEVELS BELOW AS APPLICABLE) DURING REPAIRS. INSTALL TEMPORARY SHORING TO SUPPORT AN UNFACTORED DEAD LOAD OF 600 POUNDS PER FOOT AND ALL CONSTRUCTION LIVE LOADS. ADJUST AND SUPPLEMENT SHORING ALONG DAMAGED TEE STEM TO MEET DEMAND. SHORING POSTS SHALL BE SPACED NO GREATER THAN 4'-0" OC. SHORING SHALL BE FOR 3 LEVELS MIN (OR TO GRADE LEVEL). SHORE/RESHORE LOADS ON CONCRETE SLAB-ON-GRADE SHALL BE DISTRIBUTED BY STEEL GRILLAGE OR TIMBER GRILLAGE SO AS NOT TO EXCEED 1500 PSF.
2. PERFORM TEST OPENINGS PER W.I. 8.2 AND LOCATE IN FIELD WITH ENGINEER. ALLOW ENGINEER TO OBSERVE CONDITION OF EXPOSED PRESTRESSING STRANDS. DO NOT PROCEED WITH WORK ITEM 8.3 UNLESS DIRECTED BY ENGINEER BASED ON CONDITIONS OBSERVED AT TEST OPENINGS PER W.I. 8.2.
3. SANDBLAST CORRODED PRESTRESSING STRANDS TO SSPC-SP6 STANDARD. EPOXY COAT STRANDS.
4. PLACE REPAIR CONCRETE TO REPLACE PORTION OF TEE STEM ALREADY REMOVED PER W.I. 8.2.
5. ENGAGE SPECIALIST TO PERFORM GROUND PENETRATING RADAR SCANNING TO LOCATE EMBEDDED STRANDS BEFORE PERFORMING ANY DRILLING, INCIDENTAL TO THIS WORK.
6. ROUGHEN CONCRETE TO 1/4" AMPLITUDE FOR BOND AT ENCASEMENT AREA.
7. JACK SHORING SUCH THAT MIDSPAN CAMBER OF DAMAGED TEE STEM MATCHES THAT OF THE AVERAGE CAMBER OF THE ADJACENT 3 TEE STEMS TO EACH SIDE. MEASURE CAMBER WITH SURVEYING EQUIPMENT.
8. LAY OUT HOLE LOCATIONS FOR DOWELS SUCH THAT PRESTRESSING STRANDS WILL NOT BE DAMAGED WHEN DRILLING. RECEIVE APPROVAL ON LAYOUT FROM ENGINEER PRIOR TO DRILLING.
9. DRILL AND SET IN EPOXY 3/4" DIA A36 THREADED RODS (HDG) AND DOWELS. FIELD BEND AND HOOK DOWELS WHERE REQUIRED AFTER EPOXY REACHES STRENGTH.
10. INSTALL 1 1/2" Ø THREAD BAR (ASTM A722, GR. 150) IN PVC PIPE, MILD REINFORCING STEEL, AND WIRE MESH.
11. PLACE CONCRETE.
12. AFTER CONCRETE REACHES 3,500 PSI MIN, INSTALL HDG ANCHOR PLATES AND NUTS AT A36 THREADED RODS. INSTALL ANCHOR PLATE, NUT AND GROUT PAD AT THREADED BAR.
13. ENGINEER SHALL BE ON SITE TO OBSERVE STRESSING OPERATIONS (CONTRACTOR TO PROVIDE ADVANCE NOTICE TO COORDINATE SCHEDULE) STRESS THREAD BAR WITH CALIBRATED EQUIPMENT, 5 KIPS AT A TIME ALTERNATING SIDES. STRESS EACH BAR TO A MAXIMUM TENSION OF 139.0 KIPS OR UNTIL THE TEE STEM LIFTS OFF SHORING POSTS. SNUG TIGHTEN NUTS AT THREADED RODS.
14. REMOVE SHORING, CLEAN WORK AREAS, AND REMOVE TEMPORARY SIGNAGE/BARRICADES.



- NOTES:
1. MINIMUM CAST LENGTH IS 12'-0" EACH SIDE OF CENTERLINE OF TEE SPAN AS SHOWN. PAYMENT SHALL BE PER EACH REPAIR LOCATION OF 24'-0" IN LENGTH PER W.I. 8.3.
 2. A LONGER CAST LENGTH MAY BE REQUIRED, DEPENDING ON THE CONDITION OF THE PRESTRESSING STRANDS REVEALED BY TEST OPENINGS. THE MINIMUM CAST LENGTH EACH SIDE OF CENTERLINE OF TEE SPAN SHALL BE THE LENGTH NECESSARY TO REACH THE END OF THE STRAND DAMAGE PLUS A MINIMUM LAP LENGTH OF 9'-0". PAYMENT BEYOND TOTAL REPAIR LENGTH OF 24'-0" SHALL BE PER EACH LINEAL FOOT PER W.I. 8.3A.
 3. CAST LENGTH SHALL BE SYMMETRIC EACH SIDE OF CENTERLINE, AND EQUAL TO THE LONGER OF THE CAST LENGTHS AS SPECIFIED IN NOTE #2.
 4. IF LENGTH OF DAMAGE TO STRAND ON ONE SIDE OF THE TEE CENTERLINE IS GREATER THAN 11'-0", NOTIFY ENGINEER FOR ALTERNATIVE REPAIR.


TEE STEM REPAIR -
PARTIALLY ENCASED STEM

8.3
(PS #5)






- NOTES:
1. SEE DETAIL 2/R-507 FOR INFORMATION SHOWN AND NOT NOTED

5 REPAIR SECTION



3/24/2022 2:51:23 PM J:\20-002301-00\WSU_PS_#1_2022_RepsDrawings\2022 WSU RENOVATIONS.rvt




- NOTES:
1. INSTALL SEALANT FLUSH WITH ADJACENT SURFACES WHERE TRAFFIC TOPPING IS TO BE INSTALLED.
 2. AT LOCATIONS OF SCALED SURFACE REPAIRS (W.I. 16.9), SEALANT REMOVAL/REPLACEMENT SHALL COMPLY WITH EPOXY/SAND MANUFACTURERS REQUIREMENTS. ROUT JOINTS AND INSTALL SEALANT AFTER EPOXY/SAND MATERIAL HAS BEEN INSTALLED AND CURED.

11.1 SEAL FLOOR CRACKS (PS #1, PS #4, PS #5, & PS #6)




11.2 REPLACE JOINT SEALANTS (PS #1, PS #4, PS #5, & PS #6)



10.7 SEAL ROOF LEVEL JOINT BETWEEN BAYS (PS #5)




- NOTES:
1. GRIND / REMOVE CONCRETE TO PROVIDE JOINT PROFILE SHOWN ABOVE. ACCEPTABLE TO RECEIVE JOINT SYSTEM PER MANUFACTURER (INCIDENTAL TO W.I. 10.6 AT PS #6).
 2. REPAIR SPALLS / DELAMINATIONS ALONG JOINT PER W.I. SERIES 3.0.




- NOTES:
1. SUBMIT SHOP DRAWING OF NEW PLATE FOR APPROVAL PRIOR TO ORDERING/FABRICATING.
 2. COMPLY WITH JOINT MANUFACTURER'S WRITTEN RECOMMENDATIONS.
 3. CONTRACTOR RESPONSIBLE TO DETERMINE SIZE OF JOINT WITH MANUFACTURER BASED ON INSTALLATION TEMPERATURE CONDITIONS.

10.6 REPLACE STAIR TOWER ISOLATION JOINT (PS #4 & PS #6)




10.4 EXPANSION JOINT - NOSING REPAIR (PS #4)




- NOTE:
1. GENERAL REQUIREMENTS SHOWN. SUBMIT SHOP DRAWINGS OF MANUFACTURER'S PROPOSED SYSTEM FOR APPROVAL.
 2. SEE DETAIL 10.3 FOR REMAINING INFORMATION.
 3. THIS OCCURS AT ALL COLUMNS / WALLS (TYP). CONTRACTOR TO VIF.

10.3.1 EXPANSION JOINT-ELASTOMERIC CONCRETE EDGED (PS #4)



- NOTE:
1. CONTRACTOR SHALL, WITH MANUFACTURER, VERIFY FIELD INSTALLATION WIDTH BASED ON TEMPERATURE CONDITIONS. EXISTING BLOCKOUT WIDTHS VARY. CONTRACTOR TO VERIFY IN FIELD.
 2. TOTAL ANTICIPATED JOINT MOVEMENT:
 - PS #4: 1/2 inch
 - PS #4: 1/2 inch
 3. PROVIDE SHOP DRAWINGS SHOWING ALL JOINT INTERSECTIONS, SPLICES, AND TERMINATIONS AS APPLICABLE. INCLUDE DETAIL AT AND AROUND COLUMNS. (SEE 10.3.1).
 4. TURNS AND CORNERS SHALL BE FACTORY-MITERED.
 5. GLAND SHALL BE TURNED UP INTO WALL AT ENDS TO PROMOTE POSITIVE DRAINAGE AND PROVIDE WATERTIGHT CONDITION. (INCIDENTAL).
 6. EXISTING HEADER WIDTHS VARY. CONTRACTOR TO VIF. REPAIR AS NEEDED PER W.I. SERIES 9.0. CONFIRM WITH ENGINEER & JOINT MANUFACTURER PRIOR TO START OF WORK. ADDITIONAL ELASTOMERIC HEADER MATERIAL REQUIRED AT SOUND BLOCKOUTS WIDER THAN 3/2 inch TO BE INCLUDED IN UNIT PRICE. NO EXTRAS ALLOWED.

10.3 EXPANSION JOINT-ELASTOMERIC CONCRETE EDGED (PS #4)



- NOTES:
1. EXISTING SLAB IS POURED TIGHT TO COLUMN. REMOVE CONCRETE TO CREATE NEW BLOCKOUT TO EXTEND EJ SYSTEM AROUND COLUMN TO WALL. SEE DETAIL 10.3.1 FOR EJ DETAIL @ COLUMN.
 2. P/T ANCHORS OCCUR ALONG EXPANSION JOINTS. LOCATE PRIOR TO SAWCUTTING OR CONCRETE REMOVALS. NOTIFY ENGINEER OF ANY DISCREPANCIES.
 3. REVIEW FIELD CONDITIONS ONSITE WITH ENGINEER PRIOR TO START OF THIS WORK.

9.3 EXPANSION JOINT - NEW BLOCKOUT AT ENDS (PS #4)



525 Avila Drive, Suite 1
Ann Arbor MI 48108
734.663.1070 Ph
www.walkerconsultants.com

WAYNE STATE UNIVERSITY 2022 PARKING STRUCTURES #1, #4, #5, & #6 REPAIRS AND MAINTENANCE

DETROIT, MICHIGAN

MARK	DATE	BIDDING AND CONSTRUCTION DESCRIPTION	REVISIONS
	03/24/2022		

ISSUE: BIDDING AND CONSTRUCTION
ISSUE DATE: 3/24/2022
PROJECT NO: 20-002301.00
DRAWN BY: Author
CHECKED BY: Checker
COPYRIGHT © 2022. ALL RIGHTS RESERVED. NO PART OF THIS DOCUMENT MAY BE REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT PERMISSION FROM WALKER CONSULTANTS, INC.

SHEET TITLE:
REPAIR DETAILS

R-505


SHEET NOTES

1. UNLESS SPECIFICALLY NOTED AS A SEPARATE PAID ITEM, ALL WORK SHOWN ON DRAWING SHEETS R-506 & R-507 SHALL BE INCLUDED UNDER W.I. 10.5 AND PAID AS A UNIT PRICE FOR "EACH EXPANSION JOINT" UNDER W.I. 10.5. IN GENERAL, THIS INVOLVES DETENSIONING AND RE-BUILDING THE SLAB EDGE TO ALLOW FOR REPLACEMENT OF THE SLIDE BEARING SYSTEM. ADDITIONAL CONCRETE AND TENDON REPAIRS BEYOND WHAT ARE SHOWN ON DRAWING SHEET R-506 SHALL BE PAID FOR SEPARATELY VIA UNIT PRICE WORK ITEMS.
2. ORIGINAL DRAWINGS INDICATE ADD TENDONS ARE PRESENT, ALTHOUGH IT IS UNKNOWN IF OR WHERE THE ADD TENDONS MAY OCCUR. CONTRACTOR TO PERFORM GPR TESTING AND TEST OPENINGS PRIOR TO BEGINNING WORK TO LOCATE ALL SLAB POST-TENSIONING TENDONS. NOTIFY ENGINEER OF GPR AND TEST OPENINGS FINDINGS AND TENDON/ANCHOR LOCATIONS AND LAYOUT FOR REVIEW PRIOR TO START OF WORK. ADDITIONAL POST TENSIONING AND CONCRETE REPAIRS BEYOND WHAT IS SHOWN MAY BE REQUIRED, DEPENDING ON THE FINDINGS OF THE TEST OPENINGS.
3. CONTRACTOR SHALL COMPLETE WORK SHOWN IN FOLLOWING ORDER:
- INSTALL ALL SHORING AS SHOWN ON R-507.
 - CONFIRM LOCATIONS OF ALL SLAB POST-TENSIONING TENDONS VIA GPR TESTING AND/OR TEST OPENINGS.
 - REMOVE CONCRETE TO CREATE STRESS BOX OPENINGS IN THE PATTERN SHOWN ON THE PLAN VIEW. IF ADDITIONAL TENDONS ARE PRESENT BEYOND WHAT IS DETAILED (AS DISCOVERED IN STEP 3B), CONFIRM LOCATIONS OF STRESS BOX OPENINGS IN FIELD WITH ENGINEER TO ENSURE THAT ALL TENDONS CAN BE DE-TENSIONED.
 - REMOVE CONCRETE SLAB FULL DEPTH ALONG EXPANSION JOINT EDGE AS SHOWN ON DETAIL 10.5.2. PERFORM CONCRETE REMOVALS AS NECESSARY ALONG BEAM BEARING LEDGE TO FULLY REMOVE EXISTING STEEL BEARING ASSEMBLY.
 - REPAIR BEAM BEARING LEDGE AS SHOWN IN DETAIL 10.5.2, INCLUDING INSTALLATION OF NEW SLIP BEARING ASSEMBLY.
 - REPLACE SLAB AS SHOWN ON DETAILS 10.5.1 & 10.5.2, INCLUDING INSTALLATION OF NEW POST-TENSIONING HARDWARE. ONLY THE STRESS BOXES SHALL REMAIN OPEN AFTER THIS STEP; PLACE BULKHEADS AS NECESSARY TO ENSURE STRESS BOXES DO NOT EXCEED SPECIFIED SIZE.
 - STRESS TENDONS. IF ANY TENDONS DO NOT ACHIEVE THE CALCULATED THEORETICAL ELONGATION, ALLOW TO SIT FOR 24 HOURS AND RE-STRESS POST-TENSIONING TENDONS TO ENSURE DESIRED FORCE IS MAINTAINED.
 - PLACE CONCRETE AT ALL STRESSING BOXES. SHORING MAY BE REMOVED ONCE ALL CONCRETE HAS REACHED REQUIRED COMPRESSIVE STRENGTH.
 - ONCE ALL CONCRETE IS FULLY CURED, RECOAT TRAFFIC TOPPING AND INSTALL NEW EXPANSION JOINT. PAINT EXPANSION JOINT BEAM.
4. MINIMUM INITIAL CONCRETE STRENGTH AT TIME OF STRESSING SHALL BE 3,500 PSI.
5. STRESS BOXES ARE SHOWN AT ESTIMATED LOCATION WHERE TENDON IS AT SLAB MID-DEPTH. CONTRACTOR MAY SHIFT STRESS BOX OPENINGS ALONG TENDON RUN AS REQUIRED TO MAINTAIN CLEAR COVER FOR STRESSING HARDWARE.
6. WHERE EXISTING TRAFFIC COATING IS DAMAGED OR EXCESSIVELY WORN AS A RESULT OF CONTRACTOR'S OPERATIONS, CONTRACTOR SHALL BE RESPONSIBLE FOR RECOATING TRAFFIC TOPPING. NO EXTRAS ALLOWED.




- NOTES:
1. BEAM SHOWN IN THE PHOTO IS THE EXPANSION JOINT BEAM SUPPORTING LEVEL 2 FLOOR SLAB WHERE W.I. 10.5 OCCURS. CONTRACTOR IS RESPONSIBLE FOR PROTECTING THE UTILITY LINES PASSING THROUGH THE BEAM (OR REPLACEMENT AT CONTRACTORS OPTION AT NO ADDITIONAL COST). CONTRACTOR SHALL BE RESPONSIBLE FOR REPLACEMENT OF ANY DAMAGED LINES AT NO EXTRA COST TO OWNER.


UTILITIES AT LEVEL 2
EXPANSION JOINT BEAM



FLOOR REPAIR -
PLAN @ STRESSING POCKET




NEW CONSTRUCTION



DEMOLITION

EXP JT - REPLACE STEEL BEARING
ANGLES W/ SLIP BEARING SYSTEM


(SECTION AT SLAB REBUILD)



NOTE:
BEAM REINF STEEL & P/T TENDONS NOT SHOWN. SEE ORIGINAL DRAWINGS

EXP JT - REPLACE STEEL BEARING
ANGLES W/ SLIP BEARING SYSTEM

(SECTION AT NEW TENDON)



EXP JT - REPLACE STEEL BEARING
ANGLES W/ SLIP BEARING SYSTEM

10.5



525 Ave Drive, Suite 1
Ann Arbor MI 48108
734.663.1070 Ph
www.walkerconsultants.com

WAYNE STATE UNIVERSITY
2022 PARKING STRUCTURES
#1, #4, #5, & #6 REPAIRS AND MAINTENANCE

DETROIT, MICHIGAN


MARK	DATE	DESCRIPTION	REVISIONS
	03/24/2022	BIDDING AND CONSTRUCTION	

ISSUE: BIDDING AND CONSTRUCTION
ISSUE DATE: 3/24/2022
PROJECT NO: 20-002301.00
DRAWN BY: Author
CHECKED BY: Checker
COPYRIGHT © 2022. ALL RIGHTS RESERVED. NO PART OF THIS DOCUMENT MAY BE REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT PERMISSION FROM WALKER CONSULTANTS, INC.


SHEET TITLE:
REPAIR DETAILS -
W.I. 10.5

R-506


J:\20-002301-00-WSU_PS_#1_2022_Rpts\Drawings\2022 WSU RENOVATIONS.mxd 3/24/2022 2:51:23 PM



1 TYPICAL SHORING LAYOUT PLAN
(FOR WI 10.5)



2 ISOMETRIC VIEW
TYPICAL WORK AREA SHORING



3 ISOMETRIC VIEW
WORK AREAS REQUIRING SHORING

SHEET NOTES

1. INSTALL TEMPORARY SHORING PER REQUIREMENTS OF W.I. 10.5 AND AS REQUIRED ON THIS SHEET. TYPICAL TEMPORARY SHORING LAYOUT PER W.I. 10.5 SHOWN ON THIS PLAN APPLIES WHEREVER THE SLAB IS DETENSIONED AS PART OF W.I. 10.5. TEMPORARY SHORING SHALL BE INSTALLED MINIMUM (3) LEVELS BELOW W.I. 10.5 WORK AREAS; SEE 2/R-507.
2. SEE 3/R-507 FOR ISOMETRIC VIEW OF ALL WORK AREAS REQUIRING TEMPORARY SHORING AS SHOWN.
3. TEMPORARY SHORING MUST BE INSTALLED PRIOR TO POST-TENSIONED TENDON DE-TENSIONING AT START OF CONCRETE DEMOLITION WORK.
4. SHORING SHOWN IS MINIMUM REQUIREMENTS AND IS BASED ON 25 PSF CONSTRUCTION LIVE LOAD AT ONE LEVEL PLUS DEAD LOAD AT ONE LEVEL. AT CONTRACTOR'S OPTION, ADDITIONAL SHORING TO SUPPORT CONSTRUCTION LIVE LOADS ABOVE 25 PSF SHALL BE DESIGNED AND SEALED BY A LICENSED PROFESSIONAL ENGINEER. NO EXTRA PAYMENT SHALL BE PROVIDED FOR THIS ADDITIONAL SHORING.
5. REFER TO R-002 "PHASING PLANS AND NOTES" FOR COORDINATION OF WORK.
6. UNFACTORED DESIGN LOAD PER SHORE INCLUDING DEAD LOAD AND CONSTRUCTION LIVE LOAD STATED IN NOTE 4 IS 5,000 LB AT REQUIRED SHORE HEIGHT (TYP.)
7. SHORES ON CONSECUTIVE LEVELS SHALL BE PLUMB AND CONCENTRICALLY LOADED WITH SHORES ABOVE AND BELOW.
8. INSTALL SHORES TIGHT TO FLOOR AND CEILING. SECURE AT TOP AND BOTTOM TO MAINTAIN REQUIRED POSITIONING / STABILITY.
9. DO NOT REMOVE SHORES PRIOR TO RE-STRESSING FLOOR SLAB.



525 Ave Drive, Suite 1
Ann Arbor, MI 48106
734.663.1070 Ph
www.walkerconsultants.com

WAYNE STATE UNIVERSITY
2022 PARKING STRUCTURES
#1, #4, #5, & #6 REPAIRS AND MAINTENANCE


DETROIT, MICHIGAN

REVISIONS		DESCRIPTION
MARK	DATE	
	03/24/2022	BIDDING AND CONSTRUCTION

ISSUE: BIDDING AND CONSTRUCTION
ISSUE DATE: 3/24/2022
PROJECT NO: 20-002301.00
DRAWN BY: Author
CHECKED BY: Checker
COPYRIGHT © 2022. ALL RIGHTS RESERVED. NO PART OF THIS DOCUMENT MAY BE REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT PERMISSION FROM WALKER CONSULTANTS, INC.


SHEET TITLE:
REPAIR DETAILS -
W.I. 10.5

R-507



- NOTES:
1. SURFACE PREPARATION SEQUENCE:
 - a) SCARIFY EXISTING SCALED SURFACE TO REMOVE LOOSE / DELAMINATED / DETERIORATED CONCRETE.
 - b) SHOT-BLAST SURFACE PER MANUFACTURER'S REQUIREMENTS. REVIEW PREPARED SURFACE TO VERIFY ALL LOOSE MATERIAL HAS BEEN REMOVED. SANDBLAST / WATER BLAST TO REMOVE LAITANCE IF REQUIRED BY MANUFACTURER.
 2. PERFORM ADDITIONAL SURFACE PREPARATION AS RECOMMENDED BY MANUFACTURER PRIOR TO APPLICATION (INCIDENTAL).
 3. INSTALL IN MULTIPLE LIFTS AS NECESSARY TO COMPLY WITH MANUFACTURER'S RECOMMENDATIONS.


16.9 SCALED SURFACE REPAIR (EPOXY/SAND) (PS #5 & PS #6)



- NOTE:
1. W.I. 16.2: INCLUDES REMOVAL OF COMPLETE EXISTING COATING SYSTEM TO BARE CONCRETE IN LARGE AREAS, AND INSTALLATION OF NEW COATING SYSTEM (PRIMER, BASE COAT, INTERMEDIATE COAT(S), TOP COAT) TO MATCH THICKNESS OF EXISTING COATING.
 2. W.I. 16.3: INCLUDES INSTALLATION OF PRIMER, BASE COAT, AND INTERMEDIATE COAT(S) TO BUILD UP SYSTEM ON BARE CONCRETE TO MATCH THICKNESS OF ADJACENT SYSTEM, PRIOR TO RECOATING PER ALT. W.I. 16.4.

16.2.1 TRAFFIC TOPPING - REPLACE EXISTING SYSTEM (PS #1 & PS #4)

16.3 TRAFFIC TOPPING - REPAIR (PS #1, PS #4, PS #5 & PS #6) (INCIDENTAL)




- NOTE:
1. QUANTITIES BASED ON HORIZONTAL APPLICATION AREA. VERTICAL DETAILING AND ADDITIONAL DETAIL COAT OVER CRACKS ARE INCIDENTAL TO THIS WORK.
 2. W.I. 16.1 REQUIRES INSTALLING NEW COATING SYSTEM ON BARE CONCRETE SURFACES.
 3. W.I. 16.2 INCLUDES REMOVAL OF EXISTING COATING SYSTEM TO BARE CONCRETE, AND INSTALLATION OF NEW COATING SYSTEM PER GENERAL REQUIREMENTS OF W.I. 16.1.
 4. W.I. 16.4 INCLUDES INSTALLING NEW INTERMEDIATE & TOP COATS ON PREPARED EXISTING COATING.
 5. REFER TO SECTION 020010 FOR SPECIFIC REQUIREMENTS.

16.1 TRAFFIC TOPPING- NEW SYSTEM (PS #4, PS #5, & PS #6) (BASE BID & ALTERNATE)


16.2 TRAFFIC TOPPING - REPLACE EXISTING SYSTEM (PS #1, & PS #4) (ALTERNATE)

16.4 TRAFFIC TOPPING - RECOAT (PS #1, PS #4, & PS #5)




- NOTES:
1. REMOVE EXISTING COVE SEALANT MATERIAL (INCIDENTAL). PREPARE SURFACE PER SPECIFICATIONS.

11.7 COVE SEALANT (PS#1, PS#4, PS#5, & PS#6)




- NOTES:
1. CLEAN JOINT SUBSTRATE BY SAND & AIR BLASTING.
 2. PREPARE AND PRIME SEALANT CAVITY & INSTALL SEALANT ACCORDING TO SEALANT MANUFACTURER'S RECOMMENDATIONS.
 3. JOINT WIDTHS VARY. CONTRACTOR TO VERIFY IN FIELD.
 4. APPLIES TO BOTH VERTICAL AND HORIZONTAL JOINT CONDITIONS.
 5. MULTIPLE CUSTOM COLORS REQUIRED. COLORS TO BE AS SELECTED BY OWNER BASED ON MOCKUPS.

11.6 SILICONE SEALANTS (PS #5, & PS #6)




- NOTES:
1. INSERT PACKERS INTO CLEAN DRILLED HOLE SO THAT TOP OF RUBBER SLEEVE IS BELOW CONCRETE SURFACE.
 2. AFTER GROUTING PROCEDURE IS COMPLETE, REMOVE PACKER AND FITTINGS FROM HOLE AND REMOVE EXCESS GROUT FROM FACE OF WALL.
 3. PATCH REMAINING HOLES WITH TROWEL APPLIED MORTAR. FILL ENTIRE HOLE FLUSH WITH SURFACE OF THE WALL TO MATCH THE EXISTING CONDITION.

11.5.1 EPOXY INJECTION (PS #5 & PS #6)



- NOTES:
1. CLEAN SURFACE OF WALL TO IDENTIFY CRACK. DRILL INJECTION PORT AT A 45° ANGLE TO INTERSECT CRACK AT THE MID-DEPTH OF THE WALL.
 2. STAGGER DRILL HOLES FROM ONE SIDE OF THE CRACK TO THE OTHER AT A MAXIMUM 12\"/>
 3. FLUSH DRILL HOLES w/CLEAN WATER. SEE DETAIL 11.5.1 FOR ADDITIONAL INFORMATION.

11.5 EPOXY INJECTION (PS #5 & PS #6)



- NOTES:
1. MATCH EXISTING JOINTS LAYOUT. TOOLING AND SEALING CONTROL JOINTS IS INCIDENTAL TO ALL CONCRETE REPAIR WORK, AND IS NOT A SEPARATE PAY ITEM.
 2. CONTROL JOINT (C.J.) MUST BE TOOLED IN PLASTIC CONCRETE AND DIMENSIONS AS DETAILED WILL BE MAINTAINED IN SET CONCRETE. SAWCUTTING OF CONTROL JOINT IN HARDENED CONCRETE WILL NOT BE PERMITTED.


11.4 TOOL AND SEAL CONTROL JOINTS (FOR REFERENCE ONLY) (PS#1, PS#4, PS#5, & PS#6) (INCIDENTAL)

WAYNE STATE UNIVERSITY
2022 PARKING STRUCTURES
#1, #4, #5, & #6 REPAIRS AND MAINTENANCE
DETROIT, MICHIGAN

BIDDING AND CONSTRUCTION DESCRIPTION		REVISIONS
MARK	DATE	
	03/24/2022	

ISSUE: BIDDING AND CONSTRUCTION	
ISSUE DATE:	3/24/2022
PROJECT NO:	20-002301.00
DRAWN BY:	Author
CHECKED BY:	Checker
COPYRIGHT © 2022. ALL RIGHTS RESERVED. NO PART OF THIS DOCUMENT MAY BE REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT PERMISSION FROM WALKER CONSULTANTS, INC.	


SHEET TITLE:
REPAIR DETAILS



- NOTES:
1. THE COMBINATION OF TENDON REPAIRS SHOWN ABOVE TYPICALLY OCCUR WHEN TENDON FAILURE OCCURS AT THE END ANCHOR ONLY OR WHEN TENDON FAILURE OCCURS AT THE END ANCHOR AND AT ANOTHER LOCATION ALONG THE SAME TENDON.
 2. STRESSING OCCURS AT CENTER-PULL COUPLING PER W.I. 21.6.
 3. NEW TENDON LENGTH BEYOND 10'-0" SHALL BE PAID FOR UNDER W.I. 21.9 IF REQUIRED.
 4. REMOVE & REPLACE CONCRETE WITHIN SECTIONS SHOWN SHADED (PERFORMED & PAID FOR UNDER W.I. SERIES 3.0).

P/T TENDON END ANCHORAGE (DEAD) TENDON SPLICE COUPLING (CENTER-PULL) (FOR REFERENCE ONLY) (PS #4)


21.4.2 21.6.1



- WORK SEQUENCE NOTES:
1. VERIFY TENDON FULLY DETENSIONED
 2. REMOVE AND REPLACE CONCRETE FULL DEPTH PER W.I. 3.3B.
 3. INSTALL NEW END ANCHOR AND REINFORCEMENT.
 4. PLACE CONCRETE AND ALLOW ADEQUATE CONC. STRENGTH GAIN PRIOR TO STRESSING.
 5. STRESS P/T TENDON. (NOT INCLUDED IN W.I. 21.4).

P/T TENDON END ANCHORAGE (DEAD)


21.4.1 (FOR REFERENCE ONLY) (PS #4)



- NOTES:
1. THIS DETAIL TYPICALLY APPLIES WHEN A TENDON FAILURE OCCURS NEAR AN EXISTING END ANCHOR AND STRESSING OF THE TENDON WILL OCCUR AT A DIFFERENT LOCATION AS DETERMINED BY ENGINEER. SEE DETAIL 21.4.1 FOR ADDITIONAL INFORMATION.
 2. THIS REPAIR WILL BE PERFORMED IN COMBINATION WITH W.I. 21.6 FOR STRESSING OF THE TENDON.
 3. ANCHOR INSTALLATION SHALL BE AT ORIGINAL TENDON ANCHOR LOCATION.
 4. CONCRETE REPAIR WORK SHALL BE PERFORMED & PAID FOR UNDER W.I. SERIES 3.0. SUPPLEMENTAL REINFORCEMENT SHOWN SHALL BE INCIDENTAL TO THIS WORK.


P/T TENDON END ANCHORAGE (DEAD)

21.4 (PS #4)



PROTECT EXPOSED P/T TENDON

21.2 (INCIDENTAL) (PS #4)



ZONE I - END ANCHOR REPAIR @ EXPANSION JOINT

- CASE 1:
A. REPLACE END ANCHOR (DEAD), AND TENDON SPLICE REPAIR.
B. SEE DETAIL SERIES 21.4 & 21.6.

ZONE II - TENDON REPAIR @ SLAB SOFFIT

- CASE 2A:
A. SINGLE COUPLING AND TENDON SPLICE REPAIR.
B. SEE DETAIL SERIES 21.6 & 21.7.

ZONE III - TENDON REPAIR OVER BEAMS

- CASE 3A:
A. SINGLE OR DOUBLE COUPLING AND TENDON SPLICE REPAIR.
B. SEE DETAIL SERIES 21.6, 21.7, & 21.8.

CASE 3C:

- A. SINGLE COUPLING TENDON SPLICE WITH CENTER-PULL TENDON SPLICE COUPLING. (KEEP INTERMEDIATE ANCHOR)
B. SEE DETAIL SERIES 21.6, & 21.7.

CASE 3D:


- A. SINGLE COUPLING TENDON SPLICE WITH CENTER-PULL TENDON SPLICE COUPLING. (REMOVE INTERMEDIATE ANCHOR)
B. SEE DETAIL SERIES 21.6 & 21.7.

NOTES:

1. TYPICAL CONCRETE DELAMINATIONS SHOWN IN CROSSHATCHED AREAS ABOVE.
2. SECTION ABOVE SHOWS TYPICAL P/T TENDON FAILURE AREAS ("ZONES"). CORRESPONDING REPAIR SCENARIOS ("CASES") ARE DESCRIBED ABOVE AND ASSOCIATED REPAIR DETAILS ARE REFERENCED.
3. A COMBINATION OF REPAIR "CASES" MAY BE REQUIRED TO REPAIR A TENDON DEPENDING ON LOCATION AND NUMBER OF FAILURES ALONG A TENDON RUN.
4. SEE "P/T REPAIR GENERAL NOTES" FOR FURTHER REQUIREMENTS.

P/T SLAB SECTION WITH TYPICAL TENDON FAILURE CONDITIONS AND REPAIR SCENARIOS


21.0 (PS #4)



- NOTE:
1. USE EXTREME CAUTION REMOVING CONCRETE AROUND TENDON ANCHOR. MAXIMUM 15# CHIPPING HAMMERS SHALL BE USED IN REMOVING CONCRETE. MULTIPLE/BUNDLED TENDON ANCHORS MAY BE ENCOUNTERED.
 2. IF DELAMINATIONS EXTEND BEYOND REMOVAL LIMITS SHOWN, P/T TENDON SHALL BE DE-TENSIONED PRIOR TO REMOVALS.

CONCRETE REMOVALS AT P/T TENDON ANCHORAGE

21.0.2 (PS #4) (FOR REFERENCE ONLY)



- NOTE:
1. WHEN PERFORMING CONCRETE REMOVALS ALONG P/T TENDON, PROVIDE TENDON SUPPORTS AS SHOWN AT 2'-0" O.C. MAX. TO MAINTAIN TENDON PROFILE (INCIDENTAL).

CONCRETE REMOVALS AT P/T CABLE

21.0.1 (PS #4) (FOR REFERENCE ONLY)



525 Avila Drive, Suite 1
Ann Arbor MI 48108
734.663.1070 Ph
www.walkerconsultants.com

WAYNE STATE UNIVERSITY
2022 PARKING STRUCTURES
#1, #4, #5, & #6 REPAIRS AND MAINTENANCE

DETROIT, MICHIGAN

MARK	DATE	BIDDING AND CONSTRUCTION DESCRIPTION	REVISIONS
	03/24/2022		

ISSUE: BIDDING AND CONSTRUCTION
ISSUE DATE: 3/24/2022
PROJECT NO: 20-002301.00
DRAWN BY: Author
CHECKED BY: Checker
COPYRIGHT © 2022. ALL RIGHTS RESERVED. NO PART OF THIS DOCUMENT MAY BE REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT PERMISSION FROM WALKER CONSULTANTS, INC.

SHEET TITLE:
REPAIR DETAILS

R-509

- NOTES:**
1. WORK LOCATION IS LEVEL 1 SOUTHEAST CORNER NEAR THE ELEVATOR LOBBY, INTERIOR WALL FACE.
 2. CONTRACTOR IS RESPONSIBLE TO PAINT NEW BLOCK/MORTAR TO MATCH EXISTING. SEE SECTION 020010 FOR MORE INFORMATION.
 3. PERFORM WORK DURING OFF HOURS. COORDINATE WITH WSU.

- NOTES:**
1. USE SERVICE WEIGHT CAST IRON PIPE. ALL MATERIAL SHALL BE IN ACCORDANCE WITH PREVAILING BUILDING ORDINANCES.
 2. INSTALL ADJUSTABLE HANGERS AS REQ'D. VERIFY MIN. HEIGHT RESTRICTIONS PRIOR TO INSTALLATION.
 3. KEEP PIPE TIGHT TO CEILING AT DRAIN WITH REQ'D. SLOPE TO R.W.C.
 4. SET DRAIN ELEVATIONS PRIOR TO PLACING CONCRETE TO ENSURE PROPER DRAINAGE (INCIDENTAL).
 5. CONCRETE WORK AND SUPPLEMENTAL REINFORCEMENT REQUIRED ON THIS DETAIL SHALL BE CONSIDERED INCIDENTAL TO WIS 25.2 & 25.3, AND ARE NOT ELIGIBLE FOR PAYMENT UNDER ANY OTHER WORK ITEMS.
 6. CONCRETE REMOVALS SHALL BE PERFORMED BY CONVENTIONAL CHIPPING HAMMERS. SAW-CUTTING OR CORING THROUGH THE SLAB IS NOT ALLOWED. DO NOT CUT ANY EXISTING REINFORCEMENT WITHOUT PRIOR WRITTEN APPROVAL FROM ENGINEER.
 7. LOCATE SUPPLEMENTAL DRAIN AT LOW POINT OF PONDING WATER.

- NOTES:** AS POSSIBLE, MAINTAIN 1/8" PER FT. MINIMUM PITCH. CLEAR-OUT
1. USE SCHEDULE 80 PVC PIPE. ALL MATERIALS SHALL BE IN ACCORDANCE WITH PREVAILING BUILDING ORDINANCES.
 2. INSTALL ADJUSTABLE HANGERS AS REQUIRED. VERIFY MINIMUM HEIGHT RESTRICTIONS OF PREVAILING BUILDING ORDINANCES PRIOR TO INSTALLATION.
 3. FULL DEPTH CONCRETE & SUPPLEMENTAL REINFORCEMENT TO BE PAID UNDER W.I. SERIES 3.0. DO NOT CUT OR DAMAGE ANY EMBEDDED ITEMS. PRECAST FIELD-TOPPED CONDITION SHOWN. SIMILAR REQUIREMENTS APPLY AT PS #4 / PS #6.
 4. REPLACEMENT/SUPPLEMENTAL DRAIN (PS #5, PS #6):
 - a. SMITH 2140-C-M-B (+2646Y)
 - b. WADE 1200-S-27-31
 - c. OR ENGINEER APPROVED EQUIVALENT
 5. REPLACEMENT/SUPPLEMENTAL DRAIN (PS #4):
 - a. 8.5" DRAIN: SMITH 2120-C-M-B (+2646Y)
 - b. 14" DRAIN: SMITH 2143-C-M-B
 - c. OR ENGINEER-APPROVED EQUIVALENT
 - d. BASE BID: 1" DRAIN IS 8.5", 2" DRAINS ARE 14".
 - e. ALTERNATE: ALL DRAINS ARE 8.5".
 - f. AT CONTRACTOR'S OPTION, 12" DRAIN SPECIFIED AT OTHER STRUCTURES MAY BE USED IN LIEU OF 8.5" DRAINS. 14" DRAIN CANNOT BE DOWNSIZED.
 6. W.I. 25.4: LOCATE DRAIN AT LOW POINT OF PONDING WATER BY FLOOD TESTING..

- NOTES:
1. IF TWO OR MORE FAILED BUNDLED TENDONS ARE ENCOUNTERED, STAGGER THE COUPLERS AS REQ'D. FOR STRESSING OPERATIONS. STRESS TENDON(S) PER W.I. 21.3 OR 21.6 AS DIRECTED BY ENGINEER.
 2. PROVIDE UP TO 10'-0" OF NEW TENDON INCIDENTAL TO THIS W.I. NEW TENDON LENGTH BEYOND 10'-0" SHALL BE PAID FOR UNDER W.I. 21.9. CONCRETE REPAIR WORK SHALL BE PERFORMED AND PAID FOR UNDER WORK ITEM SERIES 3.0.


- NOTES:** **PARTIAL FLOOR PLAN**
1. SEE DETAILS 21.4, 21.4.1, 21.6.1 & 21.7.1 FOR ADDITIONAL INFORMATION.
 2. INCREASE CONCRETE REMOVAL LENGTH AS REQUIRED BY STRESSING AND INSTALLATION METHODS.
 3. CONCRETE REPAIRS SHALL BE PERFORMED AND PAID FOR UNDER WORK ITEM SERIES 3.0.
 4. STAGGER SPlice COUPLERS IF MORE THAN (1) TENDON PER RUN REQUIRES REPAIR. MAY NEED TO ALTERNATE CENTER-PULL COUPLERS ON OPPOSITE SIDES OF GRID LINE.
 5. LOCATE SPlice COUPLINGS ALONG EXIST. TENDON PROFILE AT SLAB MID-DEPTH (APPROX. 6'-0" FROM GRID LINE) IF NEEDED.
 6. NEW TENDON LENGTH BEYOND 10'-0" SHALL BE PAID FOR UNDER W.I. 21.9.

- NOTES:**
1. THE COMBINATION OF TENDON REPAIRS SHOWN ABOVE TYPICALLY OCCUR WHEN TENDON FAILURE OCCURS AT THE END ANCHOR ONLY OR WHEN TENDON FAILURE OCCURS AT THE END ANCHOR AND AT ANOTHER LOCATION ALONG THE SAME TENDON.
 2. PULL TENDON BACK IN ORDER TO POSITION NEW END ANCHOR IN ORIGINAL LOCATION. STRESSING OCCURS AT CENTER-PULL COUPLING PER W.I. 21.6.
 3. NEW TENDON LENGTH BEYOND 10'-0" SHALL BE PAID FOR UNDER W.I. 21.9 AS APPROPRIATE.
 4. REMOVE & REPLACE CONCRETE WITHIN SECTIONS SHOWN SHADED (PERFORMED & PAID FOR UNDER W.I. SERIES 3.0.

[illegible]

ISSUE: BIDDING AND CONSTRUCTION	
ISSUE DATE:	3/24/2022
PROJECT NO:	20-002301.00
DRAWN BY:	ECC
CHECKED BY:	DJP
COPYRIGHT © 2022. ALL RIGHTS RESERVED. NO PART OF THIS DOCUMENT MAY BE REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT PERMISSION FROM WALKER CONSULTANTS, INC.	


SHEET TITLE:
REPAIR DETAILS



- NOTES:
1. PAY UNIT INCLUDES PROVIDING CORNER UNITS, BOND BEAM UNITS, ETC. AS REQUIRED TO REPAIR ALL DAMAGED CMU.
 2. INCIDENTAL TO THIS WORK IS PROVIDING NEW TRUSS OR LADDER TYPE REINFORCEMENT TO MATCH EXISTING. LAP MINIMUM ONE BLOCK LENGTH.
 3. CONTRACTOR SHALL SUPPORT REMAINING AREAS OF CMU DURING REPAIRS.
 4. PAINT NEW UNITS TO MATCH COLOR OF EXISTING ADJACENT UNITS (INCIDENTAL).

REPLACE CONCRETE MASONRY UNITS


(PS #4) (FOR REFERENCE ONLY)



- NOTES:
1. ANGLES SHALL BE ACCURATELY ALIGNED PERPENDICULAR TO JOINT.
 2. ANGLES, SHIMS, BOLTS AND HARDWARE SHALL BE HOT-DIPPED GALVANIZED.
 3. INSTALL SHEAR CONNECTORS AS SHOWN IN VIEW "B" (7 NEW CONNECTORS AT EACH AFFECTED JOINT).
 4. LOCATE NEW SHEAR CONNECTORS TO AVOID EXISTING EMBEDDED SHEAR CONNECTORS AND REINFORCEMENT WHEN DRILLING THRU BOLTS. NO EXTRAS ALLOWED TO RELOCATE THRU BOLTS.
 5. PAYMENT FOR THIS WORK ITEM IS FOR EACH AFFECTED JOINT (7 NEW CONNECTORS AT 1 JOINT = 1 QUANTITY)

SUPPLEMENTAL SHEAR CONNECTORS

(PS #6)



- NOTES:
1. CONTRACTOR SHALL FIELD-VERIFY ALL DIMENSIONS PRIOR TO FABRICATION.
 2. W.I. 41.1A: STAIR TREADS ARE APPROXIMATELY 43.5" WIDE, V.I.F.
 3. W.I. 41.1B: STAIR TREADS ARE APPROXIMATELY 55.5" WIDE, V.I.F.
 4. W.I. 41.1C: EXISTING TREAD PLATE HAS BROKEN WELDS. CONTRACTOR SHALL PREPARE AND WELD EDGES AND RESEAL THE EDGES PER THE REQUIREMENTS SHOWN ON THIS DETAIL.
 5. REFER TO SECTION "WORK ITEMS" FOR FURTHER REQUIREMENTS.

INSTALL STAIR TREAD PLATES - WEST AND NORTHEAST TOWERS

(PS #4)

INSTALL STAIR TREAD PLATES - SOUTHWEST TOWER

(PS #4)

RE-WELD / RESEAL EXISTING STAIR TREAD PLATES


(PS #4)



- NOTES:
1. LOCATION SHOWN IS NORTHEAST STAIR TOWER, LEVEL 8. OTHER REPLACEMENT LOCATION (LEVEL 7) IS SAME CONDITION. REFERENCE SPECIFICATION SECTION 020010 "WORK ITEMS" FOR WORK REQUIREMENTS.

STAIRS - REPLACE METAL PAN LANDING / CONCRETE

(PS #4)



- NOTES:
1. PAY UNIT IS "EA." GUARD PIPE SECTION SPANNING FROM COLUMN TO CENTER SUPPORT STEEL (APPROX. 11'-6" LONG).

REPLACE CORRODED GUARD PIPE

(PS #4)



PHOTO C




PHOTO D



PHOTO B



PHOTO A



STAIR TOWERS - REPLACE LINTELS


(PS #5)

STAIR TOWERS - REPLACE CMU UNITS

(PS #5)

STAIR TOWERS - REMOVE DOOR/FRAME & RE-FINISH OPENING


(PS #5)



- NOTES:
1. REMOVE EXISTING SEALANT MATERIAL IF PRESENT (INCIDENTAL). PREPARE SURFACE PER SPECIFICATIONS.
 2. TRIANGULAR BACKER ROD OR BOND BREAKER REQUIRED AT INTERSECTION OF NON-MONOLITHIC MATERIALS.
 3. WHERE GAP IS PRESENT, PROVIDE ROUND BACKER ROD OVERSIZED TO FIT OPENING IN LIEU OF TRIANGULAR BACKER ROD (INCIDENTAL).

MASONRY - SEALANT


(PS #1)



- NOTES:
1. PRIME JOINT AS REQUIRED BY SEALANT MANUFACTURER.
 2. INSTALL SEALANT EVENLY AND TOOL JOINT CONCAVE. WET TOOLING WILL NOT BE ALLOWED.
 3. SUBMIT COLOR SAMPLES TO OWNER FOR APPROVAL PRIOR TO START OF WORK.

MASONRY - ROUTE / SEAL CRACKS

35.3




- REMOVE ALL UNSOUND OR DETERIORATED MORTAR IN HATCHED AREA AND PLACE NEW MORTAR, AS REQ'D.

- NOTES:
1. REMOVE LOOSE MORTAR MATERIAL FROM JOINT.
 2. FILL ANY VOIDS IN JOINT BEYOND POINTING WORK DEPTH.
 3. GRIND BRICK SURFACES CLEAN OF EXISTING MORTAR. DO NOT DAMAGE ADJACENT MASONRY.
 4. INSTALL MORTAR IN THREE LIFTS, COMPACTING EACH LIFT.
 5. TOOL MORTAR JOINT CONCAVE.

MASONRY - TUCKPOINTING

(PS #1 & PS #4) (FOR REFERENCE ONLY AT PS #4)



- NOTES:
1. MORTAR JOINT REPLACEMENT AT BRICK MASONRY UNIT REPLACEMENT LOCATIONS IS INCIDENTAL. NO EXTRA PAYMENT UNDER TUCKPOINTING WORK ITEM.
 2. DO NOT DAMAGE ADJACENT BRICK BY OVERCUTTING.
 3. REPLACEMENT BRICK TO BE APPROVED BY ENGINEER AND/OR OWNER PRIOR TO START OF WORK.
 4. REPLACEMENT BRICK SHALL MATCH EXISTING. SUBMIT SAMPLES FOR OWNER APPROVAL.

REMOVE / REPLACE BRICK

(PS #1)

MARK	DATE	BIDDING AND CONSTRUCTION	DESCRIPTION	REVISIONS
	03/24/2022			

ISSUE:	BIDDING AND CONSTRUCTION
ISSUE DATE:	3/24/2022
PROJECT NO:	20-002301.00
DRAWN BY:	ECC
CHECKED BY:	DJP

COPYRIGHT © 2022. ALL RIGHTS RESERVED. NO PART OF THIS DOCUMENT MAY BE REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT PERMISSION FROM WALKER CONSULTANTS, INC.

SHEET TITLE:
REPAIR DETAILS